



## eManager ACTIO 1072


eManager ACTIO 1072, ARM controller

Code: D201000012000

- > Memory: 256 MB | 512 MB NAND
- > Analogue Inputs: 7
- > Módulos: 7
- > Communications: RS232/485 | Ethernet | Wi-Fi
- > N° relays: 2 (6 A)
- > Digital inputs: 10
- > Power supply: 85 ... 264 V~
- > CPU: ARM Cortex A7 700 MHz

### Description

eManager ActIO is the range of IoT industrial controllers with different combinations of digital inputs, analogue inputs and relays. eManager ActIO centralises datalogging, communications, industrial protocol integration, signals and actuators. All in one.

All eManager input & output modules have their own microprocessor so you can perform real-time operations without relying on the main Linux CPU. In addition, you can control each relay, digital & analogue input in an agile and intuitive way with our customised Node-RED nodes.  




## eManager ACTIO 1072

Code: D201000012000

### Specifications

#### AC power supply

Consumption	8,8 ... 10,5 VA
Frequency	47 ... 63 Hz
Nominal voltage	85 ... 264 V~

#### DC power supply

Consumption	6,4 ... 6,5 W
Nominal voltage	120 ... 300 Vdc

#### Electrical characteristics

Isolation level	3 kVac
-----------------	--------

#### Mechanical characteristics

Size (mm) width x height x depth	123 x 89 x 48 (mm)
Envelope	Polycarbonate UL94 - Self-extinguishing V2
Fastening	DIN rail 46277 (EN 50022)
Weight (kg)	0,288

#### Environmental characteristics

Protection class	IP 20
Relative humidity (without condensation)	5...95 %
Working temperature	-20...+50 °C

#### Communication Network

Technology / Interface	Ethernet 10/100 Mbps
------------------------	----------------------

#### Control Unit

Clock	RTC
CPU	ARM Cortex A7 700 MHz
PSRAM Memory	256 MB
SPI Flash Memory	512 MB NAND

#### Standards

Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300 V
Electrical safety, Contamination level/class	Double-insulated electric shock protection class II (IEC 61010)
Standards	UNE EN 61010-1, UNE-EN 61000-6-2, UNE-EN 61000-6-4

#### Electrical safety

Insulation	3 kVac
------------	--------



## eManager ACTIO 1072

Code: D201000012000

### Analogue inputs

Quantity	7
Nominal range	0...10 V / 0...20 mA or 4...20 mA
Nominal input range	0...10 V / 0...20 mA or 4...20 mA

### Digital inputs

Quantity	10
Type	0...24 Vdc

### Digital relay outputs

Quantity	2
Type	NO
Maximum current	6 A
Maximum open contact voltage	250 Vac

### Serial communication

Technology / Type	RS-232 (full-duplex) / RS-485 (half-duplex) Galvanic isolation
-------------------	--

### Wireless communication

Band	802.11 b/g/n (2.4 GHz.)
Technology / Type	Wi-Fi

### eManager ActIO

IoT programmable controllers with digital, analog inputs and relays

CODE	TYPE	CPU	Memory	Analogue Inputs	Digital inputs	N° relays	Communications	Power supply
<b>eManager ActIO</b>								
D201000012000	eManager ACTIO 1072	ARM Cortex A7 700 MHz	256 MB   512 MB NAND	7	10	2 (6 A)	RS232/485   Ethernet   Wi-Fi	85 ... 264 V~
D301100012000	eManager Pro GPRS ACTIO 1072	ARM Cortex A7 800 MHz	512 MB   8 GB eMMC	7	10	2 (6 A)	RS232/485   Ethernet   Wi-Fi   GPRS	85 ... 264 V~
D301100030000	eManager Pro GPRS ACTIO 80	ARM Cortex A7 800 MHz	512 MB   8 GB eMMC			8 (2 A)	RS232/485   Ethernet   Wi-Fi   GPRS	85 ... 264 V~
D301200012000	eManager Pro 4G ACTIO 1072	ARM Cortex A7 800 MHz	512 MB   8 GB eMMC	7	10	2 (6 A)	RS232/485   Ethernet   Wi-Fi   4G EMEA	85 ... 264 V~