



eManager Pro 4G ACTIO 1072


eManager Pro 4G ACTIO 1072, ARM controller

Code: D301200012000

- > Memory: 512 MB | 8 GB eMMC
- > Analogue Inputs: 7
- > Módulos: 7
- > Communications: RS232/485 | Ethernet | Wi-Fi | 4G EMEA
- > N° relays: 2 (6 A)
- > Digital inputs: 10
- > Power supply: 85 ... 264 V~
- > CPU: ARM Cortex A7 800 MHz

Description

eManager ActIO is the range of IoT industrial controllers with different combinations of digital inputs, analogue inputs and relays. eManager ActIO centralises datalogging, communications, industrial protocol integration, signals and actuators. All in one.

All eManager input & output modules have their own microprocessor so you can perform real-time operations without relying on the main Linux CPU. In addition, you can control each relay, digital & analogue input in an agile and intuitive way with our customised Node-RED nodes.




eManager Pro 4G ACTIO 1072

Code: D301200012000

Specifications

AC power supply

Consumption	8,8 ... 10,5 VA
Frequency	47 ... 63 Hz
Nominal voltage	85 ... 264 V~

DC power supply

Consumption	6,4 ... 6,5 W
Nominal voltage	120 ... 300 Vdc

Electrical characteristics

Isolation level	3 kVac
-----------------	--------

Mechanical characteristics

Size (mm) width x height x depth	123 x 89 x 48 (mm)
Envelope	Polycarbonate UL94 - Self-extinguishing V2
Fastening	DIN rail 46277 (EN 50022)
Weight (kg)	1

Environmental characteristics

Protection class	IP 20
Relative humidity (without condensation)	5...95 %
Working temperature	-20...+50 °C

Communication Network

Technology / Interface	Ethernet 10/100 Mbps
------------------------	----------------------

Control Unit

Clock	RTC
CPU	ARM Cortex A7 800 MHz
PSRAM Memory	512 MB
SPI Flash Memory	8 GB eMMC

Standards

Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300 V
Electrical safety, Contamination level/class	Double-insulated electric shock protection class II (IEC 61010)
Standards	UNE EN 61010-1, UNE-EN 61000-6-2, UNE-EN 61000-6-4

Electrical safety

Insulation	3 kVac
------------	--------



eManager Pro 4G ACTIO 1072

Code: D301200012000

Analogue inputs

Quantity	7
Nominal range	0...10 V / 0...20 mA o 4...20 mA
Nominal input range	0...10 V / 0...20 mA or 4...20 mA

Digital inputs

Quantity	10
Type	0...24 Vdc

Digital relay outputs

Quantity	2
Type	NO
Maximum current	6 A
Maximum open contact voltage	250 Vac

Radio communication

Band	LTE-FDD B1/B3/B7/B8/B20/B28A, WCDMA B1/B8 & GSM/EDGE B3/B8
Technology / Type	4G EMEA

Serial communication

Technology / Type	RS-232 (full-duplex) / RS-485 (half-duplex)Galvanic isolation
-------------------	---

Wireless communication

Band	802.11 b/g/n (2.4 GHz.)
Technology / Type	Wi-Fi

eManager ActIO

IoT programmable controllers with digital, analog inputs and relays

CODE	TYPE	CPU	Memory	Analogue Inputs	Digital inputs	N° relays	Communications	Power supply
eManager ActIO								
D301100012000	eManager Pro GPRS ACTIO 1072	ARM Cortex A7 800 MHz	512 MB 8 GB eMMC	7	10	2 (6 A)	RS232/485 Ethernet Wi-Fi GPRS	85 ... 264 V~
D301100030000	eManager Pro GPRS ACTIO 80	ARM Cortex A7 800 MHz	512 MB 8 GB eMMC			8 (2 A)	RS232/485 Ethernet Wi-Fi GPRS	85 ... 264 V~
D301200012000	eManager Pro 4G ACTIO 1072	ARM Cortex A7 800 MHz	512 MB 8 GB eMMC	7	10	2 (6 A)	RS232/485 Ethernet Wi-Fi 4G EMEA	85 ... 264 V~