



eManager Pro Energy


eManager Pro Energy, ARM controller

Code: D302000070000

- > Memory: 512 MB | 8 GB eMMC
- > Módulos: 7
- > Communications: RS232/485 | Ethernet | Wi-Fi
- > System: 1 xThree-phase / 3 xSingle-phase
- > Power supply: 85 ... 264 V~
- > CPU: ARM Cortex A7 800 MHz

Description

eManager Energy is an industrial IoT controllers product range with integrated three-phase energy metering. eManager Energy centralizes power network analyzer features with datalogging and communications. The energy module is able to measure up to one three-phase circuit or three single-phase circuits. It integrates 4 quadrant monitoring, including the main electrical parameters for single-phase and three-phase. Measurement accuracy is Class 1 Active and Class 2 Reactive; and the secondary current is 1 A. In addition, a custom Node-RED node is available to facilitate the data collecting and displaying with a local real-time dashboard that can be accessed via their own Wi-Fi network.





eManager Pro Energy

Code: D302000070000

Specifications

AC power supply

Consumption	8,8 ... 10,5 VA
Frequency	47 ... 63 Hz
Nominal voltage	85 ... 264 V~

DC power supply

Consumption	6,4 ... 6,5 W
Nominal voltage	120 ... 300 Vdc

Electrical characteristics

Isolation level	3 kVac
-----------------	--------

Mechanical characteristics

Size (mm) width x height x depth	123 x 89 x 48 (mm)
Envelope	Polycarbonate UL94 - Self-extinguishing V2
Fastening	DIN rail 46277 (EN 50022)
Weight (kg)	0,246

Environmental characteristics

Protection class	IP 20
Relative humidity (without condensation)	5...95 %
Working temperature	-20...+50 °C

Current measurement circuit

Installation category	CAT III 300 V
Nominal current (In)	... / 1A
Phase current measuring range	2...120% de In

Voltage measurement circuit

Installation category	CAT III 300 V
Voltage measuring range	5 ... 120 % Un
Nominal voltage	285V Ph-N, 480V Ph-Ph

Communication Network

Technology / Type	Ethernet 10/100 Mbps
-------------------	----------------------

Control Unit

Clock	RTC
CPU	ARM Cortex A7 800 MHz
PSRAM Memory	512 MB



eManager Pro Energy

Code: D302000070000

SPI Flash Memory	8 GB eMMC
Standards	
Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300 V
Electrical safety, Contamination level/class	Double-insulated electric shock protection class II (IEC 61010)
Standards	UNE EN 61010-1, UNE-EN 61000-6-2, UNE-EN 61000-6-4
Electrical safety	
Insulation	3 kVac
Measurement accuracy	
Reactive energy measurement (kvarh)	Class 2
Active energy measurement (kWh)	Class 1
Serial communication	
Technology / Type	RS-232 (full-duplex) / RS-485 (half-duplex)Galvanic isolation
Wireless communication	
Band	802.11 b/g/n (2.4 GHz.)
Technology / Type	Wi-Fi

eManager Energy
IoT programmable controllers with integrated energy metering

CODE	TYPE	CPU	Memory	Communications	Power supply
eManager Energy					
D302000070000	eManager Pro Energy	ARM Cortex A7 800 MHz	512 MB 8 GB eMMC	RS232/485 Ethernet Wi-Fi	85 ... 264 V~
D302000080000	eManager Pro Energy X2	ARM Cortex A7 800 MHz	512 MB 8 GB eMMC	RS232/485 Ethernet Wi-Fi	85 ... 264 V~
D302200080000	eManager Pro 4G Energy X2	ARM Cortex A7 800 MHz	512 MB 8 GB eMMC	RS232/485 Ethernet Wi-Fi 4G EMEA	85 ... 264 V~