



## ePick GPRS VPN

---

ePick GPRS VPN, Gateway with GPRS communications via VPN network (1) and SIM card fully configured to send data from the units connected to the RS-485 port or Ethernet to the Databox cloud platform in order to carry out energy audits and improvements related to electrical energy efficiency,

Code: D60060.

### Description

---

**ePick GPRS VPN** or **ePick GPRS NET**. It is a **datalogger** or **gateway** designed to connect all of your installation's devices and sensors in order to facilitate electric energy management together with the **CIRCUTOR DataBox platform**.



## ePick GPRS VPN

Gateway for DataBox platform

Code: D60060.

### Specifications

#### AC power supply

Installation category	CAT III 300 V
Consumption	8,8 ... 10,5 VA
Frequency	47 ... 63 Hz.
Nominal voltage	85 ... 264 V~

#### DC power supply

Installation category	CAT III 300 V
Consumption	6,4 ... 6,5 W
Nominal voltage	120 ... 300 V

#### Mechanical characteristics

Size (mm) width x height x depth	87,5 x 88,5 x 48 (mm)
Envelope	PC UL 94 - V0 self-extinguishing
Fastening	DIN rail
Weight (kg)	0,18

#### Environmental characteristics

Protection class	IP 20 / IK 08
Relative humidity (without condensation)	5 ... 95 %
Storage temperature	-25 ... +75 °C
Working temperature	-20 ... +50 °C

#### Standards

Electrical safety, Maximum height (m)	2000
Electrical safety, Contamination level/class	Pollution resistance 2
Standards	UNE-EN 61000-6-4, UNE EN 61000-6-2, UNE-EN 61010-1, 2012/19/EC

#### Electrical safety

Insulation	Double-insulated electric shock protection class II (IEC 61010-1)
------------	---

#### User interface

LED	3 LED
-----	-------

ePick  
Gateway for DataBox platform



## ePick GPRS VPN

Gateway for DataBox platform

Code: D60060.

CODE	TYPE	Integrated Software	Transistor output	Generic Modbus	Communications	Protocol	Analogue Inputs	N° relays	Digital inputs	Analog output	Description
D70050.	Line-EDS-cloud	API's de	2	1	Ethernet   Wi-Fi   RS-485   Bus-Line	Modbus   API's   web					
D70005.	Line-EDS-PS	PowerStudio	2	1	Ethernet   Wi-Fi   RS-485   Bus-Line	Modbus (Circuitor + generic)   XML					
D70020.	Line-EDS-PSS PRO	PowerStudio Scada PRO	2	1	Ethernet   Wi-Fi   RS-485   Bus-Line	Modbus (Circuitor + generic)   XML					
D70021.	Line-EDS-iMonitor	PowerStudio Scada PRO + Front-end iMonitor	2	1	Ethernet   Wi-Fi   RS-485   Bus-Line	Modbus (Circuitor + generic)   XML					
<b>Input/Output Modules</b>											
D73001.	Line-M-4I0-T		4			Modbus/RTU	-	-	4	-	
D73002.	Line-M-4I0-R		-			Modbus/RTU	-	4	4	-	
D73008.	Line-M-8I60		-			Modbus/RTU	-	6	8	-	
D73003.	Line-M-4I0-A		-			Modbus/RTU	4 (0/4 ... 20 mA)	-	-	4 (0/4 ... 20 mA)   4 (0/2 ... 10 Vdc)	
D73004.	Line-M-4I0-RV		-			Modbus/RTU	-	4	4 (230 V)	-	
D73006.	Line-M-20I					Modbus/RTU		-	20		
<b>Power supply</b>											
D7300A.	Line-M-EXT-PS										110-277 V ~ (P-N)/110-480 V ~ (P-P) power supply for maximum of 3 Line devices
<b>Modem</b>											
D73007.	Line-M-3G										3G/GPRS communications modem and Bus-Line to communicate with Line-EDS devices
D7300C.	Line-M-4G										4G/GPRS communications modem and Bus-Line to communicate with Line-EDS devices
<b>Ethernet converter</b>											
D80030.	Line-TCPRS1										RS-485/RS-232 to Ethernet/Wi-Fi converter (ModbusTCP/TCP/UDP) Integrated web server and mobile app (MyConfig) for configuration
D60060.	ePick GPRS VPN										Gateway with GPRS communications via VPN network (1) and SIM card fully configured to send data from the units connected to the RS-485 port or Ethernet to the Databox cloud platform in order to carry out energy audits and improvements related to electrical energy efficiency
D60070.	ePick GPRS NET										Gateway with GPRS communications (SIM card must be provided by the user) to send data from the units connected to the RS-485 port or Ethernet to the Databox cloud platform in order to carry out energy audits and improvements related to Electrical Energy Efficiency