





ePick GPRS VPN

ePick GPRS VPN, Gateway with GPRS communications via VPN network (1) and SIM card fully configured to send data from the units connected to the RS-485 port or Ethernet to the Databox cloud platform in order to carry out energy audits and improvements related to electrical energy efficiency,

Code: D60060.

Description

ePick GPRS VPN or **ePick GPRS NET**. It is a **datalogger** or **gateway** designed to connect all of your installation's devices and sensors in order to facilitate electric energy management together with the **CIRCUTOR DataBox platform**.







ePick GPRS VPN

Gateway for DataBox platform

Gateway for DataBox platform

Code: D60060.

Specifications

AC power supply	
Installation category	CAT III 300 V
Consumption	8,8 10,5 VA
Frequency	47 63 Hz.
Nominal voltage	85 264 V~
DC power supply	
Installation category	CAT III 300 V
Consumption	6,4 6,5 W
Nominal voltage	120 300 V
Mechanical characteristics	
Size (mm) width x height x depth	87.5 x 88.5 x 48 (mm)
Envelope	PC UL 94 - V0 self-extinguishing
Fastening	DIN rail
Weight (kg)	0,244
Environmental characteristics	
Protection class	IP 20 / IK 08
Relative humidity (without condensation)	5 95 %
Storage temperature	-25 +75 °c
Working temperature	-20 +50 °c
Standards	
Electrical safety, Maximum height (m)	2000
Electrical safety, Contamination level/class	Pollution resistance 2
Standards	UNE-EN 61000-6-4, UNE EN 61000-6-2, UNE-EN 61010-1, 2012/19/EC
Electrical safety	
Insulation	Double-insulated electric shock protection class II (IEC 61010-1)
User interface	
LED	3 LED

ePick

Gateway for DataBox platform







ePick GPRS VPN

Gateway for DataBox platform

Code: D60060.

CODE	TYPE	Integrated Software	Transistor output	Generic Modbus	Communications	Protocol	Description	Analogue Inputs	N° relays	Digital inputs	Analog output
D70050.	Line-EDS-cloud	API's de	2	1	Ethernet RS-485 Bus- Line	Modbus API's web					
D70005.	Line-EDS-PS	PowerStudio	2	1	Ethernet RS-485 Bus- Line	Modbus (Circutor + generic) XML					
D70020.	Line-EDS-PSS PRO	PowerStudio Scada PRO	2	1	Ethernet RS-485 Bus- Line	Modbus (Circutor + generic) XML					
D70021.	Line-EDS-iMonitor	PowerStudio Scada PRO + Front-end iMonitor	2	1	Ethernet RS-485 Bus- Line	Modbus (Circutor + generic) XML					
Modem											
D7300C.	Line-M-4G						4G/GPRS communications modem and Bus-Line to communicate with Line-EDS devices				
Ethernet	converter										
D80030.	Line-TCPRS1						RS-485/RS-232 to Ethernet/Wi-Fi converter (ModbusTCP/TCP/UDP) Integrated web server and mobile app (MyConfig) for configuration				
Power su	pply										
D7300A.	Line-M-EXT-PS						110-277 V ~ (P-N)/110-480 V ~ (P-P) power supply for maximum of 3 Line devices				
Input/Ou	tput Modules										
D73001.	Line-M-4I0-T		4			Modbus/RTU		-	-	4	-
D73002.	Line-M-4IO-R		-			Modbus/RTU		-	4	4	-
D73008.	Line-M-8I60		-			Modbus/RTU		-	6	8	-
D73003.	Line-M-4IO-A		-			Modbus/RTU		4 (0/4 20 mA)	-	-	4 (0/4 20 mA) 4 (0/2 10 Vdc)
D73004.	Line-M-4IO-RV		-			Modbus/RTU		-	4	4 (230 V)	-
D73006.	Line-M-20I					Modbus/RTU			-	20	
D60060.	ePick GPRS VPN						Gateway with GPRS communications via VPN network (1) and SIM card fully configured to send data from the units connected to the RS-485 port or Ethernet to the Databox cloud platform in order to carry out energy audits and improvements related to electrical energy efficiency				
D60070.	ePick GPRS NET						Gateway with GPRS communications (SIM card must be provided by the user) to send data from the units connected to the RS-485 port or Ethernet to the Databox cloud platform in order to carry out energy audits and improvements related to Electrical Energy Efficiency				

