





Line-M-4IO-T, Expansion modules

Code: D73001.

> Protocol: Modbus/RTU
> Communications: Bus-Line
> Transistor output: 4
> Digital inputs: 4

> Mounting: DIN rail

Description

Module with 4 floating transistor inputs and outputs.

The expansion modules of the Line range provide a simple way to extend the features of any version of line-EDS-Cloud, line-EDS-PS, or of the line-CVM-D32 network analyser.

They allow adding digital outputs and inputs, analogue inputs and outputs or any combination thereof, to the devices.

The modules are connected laterally and are detected automatically when the lateral connection is made, which greatly simplifies the installation and configuration of the modules.

Application

- \circ Expansion of inputs/outputs from line-CVM-D32 or line-EDS network analysers.
- \circ Management of up to 4 tariffs with activation of the different inputs to the module.
- Alarms can be programmed independently based on high/low values, hysteresis, timer on/off delays, normally open or closed rest state and interlocks.
- Generation of impulses through outputs to a transistor, fully and independently configurable based on any incremental parameter of active or reactive energy, either per total counter or per tariff.
- o Track the status of components in the installation by using the status of the inputs to the module.







Module with 4 transistor inputs and outputs

Code: D73001.

Specifications

DC power supply				
Consumption	max. 4 W			
Mechanical characteristics				
Size (mm) width x height x depth	52.5 x 118 x 70 (mm)			
Envelope	Self-extinguishing V0 plastic			
Fastening	DIN rail (IEC 60715)			
Weight (kg)	0,16			
Environmental characteristics				
Protection class	IP30, Front: IP40			
Relative humidity (without condensation)	5 95%			
Storage temperature	-20 +70 °C			
Working temperature	-10 +50 °C			
Voltage measurement circuit				
Input impedance	3kΩ			
Standards				
Electrical safety, Maximum height (m)	2000			
Electrical safety, Installation category	CAT III 300 V			
Standards	UNE-EN 61010-1, UNE-EN 61000-6-2, UNE-EN 61000-6-4			
User interface				
LED	9 LED			
Digital inputs				
Input/output insulation	3,75 kV~			
Quantity	4			
Туре	Optocoupler			
Minimum signal width	10 ms			
Digital transistor outputs				
Pulse width	1 ms			
Quantity	4			
Туре	Optocoupler NO			
Maximum frequency	500 Hz			
Maximum current	120mA			
Maximum voltage	48Vcc			









Module with 4 transistor inputs and outputs

Code: D73001.

Line-M-410-TExpansion modules, Line series

CODE	TYPE	Protocol	Analogue Inputs	Transistor output	N° relays	Digital inputs	Analog output		
Input/Output Modules									
D73001.	Line-M-4I0-T	Modbus/RTU	-	4	-	4	-		

Transistor I/O expansion modules, Line system







Module with 4 transistor inputs and outputs

Code: D73001.

Dimensions Connections







