



Line-M-3G

Line-M-3G, 3G/GPRS communications modem and Bus-Line to communicate with Line-EDS devices,

Code: D73007.

Specifications

AC power supply

| | |
|-----------------------|----------------|
| Installation category | CAT III 300V |
| Consumption | 2,8 ... 4,1 VA |

DC power supply

| | |
|-------------|---------------|
| Consumption | 1,9 ... 2,2 W |
|-------------|---------------|

Mechanical characteristics

| | |
|----------------------------------|-------------------------------|
| Size (mm) width x height x depth | 35 x 93.85 x 88.95 (mm) |
| Envelope | Self-extinguishing V0 plastic |
| Fastening | DIN rail (IEC 60715) |
| Weight (kg) | 0,178 |

Environmental characteristics

| | |
|--|-------------------|
| Protection class | IP30, Front: IP40 |
| Relative humidity (without condensation) | 5 ... 95% |
| Storage temperature | -20 ... +70 °C |
| Working temperature | -10 ... +50 °C |

Standards

| | |
|--|---|
| Electrical safety, Maximum height (m) | 2000 |
| Electrical safety, Installation category | CAT III 300 V |
| Standards | UNE-EN 61010-1, UNE-EN 61000-6-2, UNE-EN 61000-6-4, UNE EN 60068-2-1, UNE EN 60068-2-2, UNE EN 60068-2-78, ETSI EN 301 489-1 Ver. 2.1.1, ETSI EN 301 489-17 Ver. 3.1.1, ETSI EN 301 489-52 Ver. 1.1.0 |

User interface

| | |
|-----|-------|
| LED | 4 LED |
|-----|-------|

Radio communication -Antenna

| | |
|--|-------------------|
| | SMA (Right Angle) |
|--|-------------------|

Radio communication

| | |
|-------------------|---------------------------------|
| Band | 850/900/1700/1800/1900/2100 MHz |
| Technology / Type | 3G |

Line-M-3G

Expansion modules, Line series



Line-M-3G

Code: D73007.

| CODE | TYPE | Description |
|--------------|-----------|--|
| Modem | | |
| D73007. | Line-M-3G | 3G/GPRS communications modem and Bus-Line to communicate with Line-EDS devices |

3G Modem, expansion modules, Line system



Line-M-3G

Code: D73007.

Dimensions

