



# Line-M-3G

Line-M-3G, 3G/GPRS communications modem and Bus-Line to communicate with Line-EDS devices,

Code: D73007.    **DESCATALOGADO**

## Specifications

### AC power supply

Installation category	CAT III 300V
Consumption	2,8 ... 4,1 VA

### DC power supply

Consumption	1,9 ... 2,2 W
-------------	---------------

### Mechanical characteristics

Size (mm) width x height x depth	35 x 93.85 x 88.95 (mm)
Envelope	Self-extinguishing V0 plastic
Fastening	DIN rail (IEC 60715)
Weight (kg)	0,178

### Environmental characteristics

Protection class	IP30, Front: IP40
Relative humidity (without condensation)	5 ... 95%
Storage temperature	-20 ... +70 °C
Working temperature	-10 ... +50 °C

### Standards

Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300 V
Standards	UNE-EN 61010-1, UNE-EN 61000-6-2, UNE-EN 61000-6-4, UNE EN 60068-2-1, UNE EN 60068-2-2, UNE EN 60068-2-78, ETSI EN 301 489-1 Ver. 2.1.1, ETSI EN 301 489-17 Ver. 3.1.1, ETSI EN 301 489-52 Ver. 1.1.0

### User interface

LED	4 LED
-----	-------

### Radio communication -Antenna

SMA (Right Angle)
-------------------

### Radio communication

Band	850/900/1700/1800/1900/2100 MHz
Technology / Type	3G

3G Modem, expansion modules, Line system



## Line-M-3G

Code: D73007.

## Dimensions

