



Line-M-8I60

Line-M-8I60, Expansion modules

Code: D73008.

- > Protocol: Modbus/RTU
- > Communications: Bus-Line
- > N° relays: 6
- > Digital inputs: 8
- > Mounting: DIN rail

Description

Module with 8 inputs and 6 outputs floating relay.

The expansion modules of the Line range provide a simple way to extend the features of any version of line-EDS-Cloud, line-EDS-PS.

They allow adding digital outputs and inputs, analogue inputs and outputs or any combination thereof, to the devices.

The modules are connected laterally and are detected automatically when the lateral connection is made, which greatly simplifies the installation and configuration of the modules.

Application

- Expansion of inputs/outputs from line-EDS network analysers.
- Alarms can be programmed independently based on high/low values, hysteresis, timer on/off delays, normally open or closed rest state and interlocks.
- Track the status of components in the installation by using the status of the inputs to the module.



Line-M-8I60

Module with 8 inputs and 6 relay outputs

Code: D73008.

Specifications

DC power supply

Consumption	max. 4 W
-------------	----------

Mechanical characteristics

Size (mm) width x height x depth	52.5 x 118 x 70 (mm)
Envelope	Self-extinguishing V0 plastic
Fastening	DIN rail
Weight (kg)	0,2

Environmental characteristics

Protection class	IP30, Front: IP40 IK08
Relative humidity (without condensation)	5 ... 95%
Storage temperature	-20 ... +70 °C
Working temperature	-10 ... +50 °C

Voltage measurement circuit

Input impedance	3kΩ
-----------------	-----

Standards

Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300 V
Standards	UNE-EN 61010-1, UNE-EN 61000-6-2, UNE-EN 61000-6-4

User interface

LED	15 LED
-----	--------

Digital inputs

Input/output insulation	3,75 kV~
Quantity	8
Type	Optocoupler
Minimum signal width	10 ms

Digital relay outputs

Quantity	6
Type	Class A, high frequency current filtering
Maximum current	5 A ~
Maximum open contact voltage	250 V ~ / 30 Vdc
Mechanical life	5 x 10 ⁶ Cycles
Maximum switching capacity	1250 VA / 150 W



Line-M-8I60

Module with 8 inputs and 6 relay outputs

Code: D73008.

Line-M-8I60

Expansion modules, Line series

CODE	TYPE	Protocol	Analogue Inputs	Transistor output	N° relays	Digital inputs	Analog output
Input/Output Modules							
M58E08.	Line-M-8I60	Modbus/RTU	-	-	6	8	-
D73008.	Line-M-8I60	Modbus/RTU	-	-	6	8	-

Relay I/O expansion modules, Line system



Line-M-8I60

Module with 8 inputs and 6 relay outputs

Code: D73008.

Dimensions



Connections

