





TCPRS1+PSDC

TCPRS1+PSDC, RS-485 / Ethernet converter / Wi-Fi

Code: D80011.

> Protocol: TCP |UDP|Modbus TCP|HTTP (Web server)-REST

> Communications: Ethernet, Wi-Fi

Description

The TCPRS1+ is a gateway designed to convert a physical environment (RS-485) to Ethernet and/or Wi-Fi. The device features a Web Server and the "MyConfig Wifi" app (Android), from which the user can fully edit the configuration parameters of the device.

Other features:

- o The device is for installation inside a medium or low voltage electric panel or enclosure, with DIN rail mounting (IEC 60715).
- $\circ~$ The TCPRS1+ comes with DHCP enabled by default.
- o Connect up to 32 devices on the RS-485 communications bus.

Application

For any installation that has multiple RS-485 communications devices that require monitoring via Wi-Fi or Ethernet.







TCPRS1+PSDC

RS-485 to Ethernet converter / Wi-Fi

Code: D80011.

Specifications

CAT III 50V
2 2,5 W
10 36 Vdc
35 x 109.45 x 70 (mm)
Self-extinguishing V0 plastic
DIN rail
0,192
IP30, Front: IP40 IK08
5 95%
-20 +70 °C
-20 +60 °C
TCP UDP Modbus TCP HTTP (Web server)-REST
Ethernet
Ethernet
culernet
2000
2000 EN 62368-1:2020/A11:2020/ AC:2020-05, ETSI EN 301 489-1 V2.2.3, ETSI EN 301 489-17 V3.2.6, ETSI EN 300 328 V2.2.2, UNE-EN IEC 62311, UNE-EN 60068-2-78, UNE-EN 60068-2-1, UNE-EN 60068-2-2, UNE-EN 61010-1, UNE-EN 61000-4-2, UNE-EN 61000-4-4, UNE-EN 61000-4-5, UNE-EN 61000-4-6, UNE-EN
2000 EN 62368-1:2020/A11:2020/ AC:2020-05, ETSI EN 301 489-1 V2.2.3, ETSI EN 301 489-17 V3.2.6, ETSI EN 300 328 V2.2.2, UNE-EN IEC 62311, UNE-EN 60068-2-78, UNE-EN 60068-2-1, UNE-EN 60068-2-2, UNE-EN 61010-1, UNE-EN 61000-4-2, UNE-EN 61000-4-4, UNE-EN 61000-4-5, UNE-EN 61000-4-6, UNE-EN
2000 EN 62368-1:2020/A11:2020/ AC:2020-05, ETSI EN 301 489-1 V2.2.3, ETSI EN 301 489-17 V3.2.6, ETSI EN 300 328 V2.2.2, UNE-EN IEC 62311, UNE-EN 60068-2-78, UNE-EN 60068-2-1, UNE-EN 60068-2-2, UNE-EN 61010-1, UNE-EN 61000-4-2, UNE-EN 61000-4-4, UNE-EN 61000-4-5, UNE-EN 61000-4-6, UNE-EN 61000-4-8, UNE-EN 61000-4-20, UNE-EN 55016-2-1.
2000 EN 62368-1:2020/A11:2020/ AC:2020-05, ETSI EN 301 489-1 V2.2.3, ETSI EN 301 489-17 V3.2.6, ETSI EN 300 328 V2.2.2, UNE-EN IEC 62311, UNE-EN 60068-2-78, UNE-EN 60068-2-1, UNE-EN 60068-2-2, UNE-EN 61010-1, UNE-EN 61000-4-2, UNE-EN 61000-4-4, UNE-EN 61000-4-5, UNE-EN 61000-4-6, UNE-EN 61000-4-8, UNE-EN 61000-4-20, UNE-EN 55016-2-1.
2000 EN 62368-1:2020/A11:2020/ AC:2020-05, ETSI EN 301 489-1 V2.2.3, ETSI EN 301 489-17 V3.2.6, ETSI EN 300 328 V2.2.2, UNE-EN IEC 62311, UNE-EN 60068-2-78, UNE-EN 60068-2-1, UNE-EN 60068-2-2, UNE-EN 61010-1, UNE-EN 61000-4-2, UNE-EN 61000-4-4, UNE-EN 61000-4-5, UNE-EN 61000-4-6, UNE-EN 61000-4-8, UNE-EN 61000-4-20, UNE-EN 55016-2-1.

TCPRS1+





Page 3 of 4





TCPRS1+PSDC

RS-485 to Ethernet converter / Wi-Fi

Code: D80011.

RS-485 / Ethernet / Wi-Fi converter

CODE	TYPE	Communications	Protocol	
Ethernet				
D80010.	TCPRS1+	RS-485, Ethernet, Wi-Fi	TCP/IP UDP Modbus TCP/IP HTTP (Web server)	
D80011.	TCPRS1+PSDC	RS-485, Ethernet, Wi-Fi	TCP UDP Modbus TCP HTTP (Web server)-REST	







TCPRS1+PSDC

RS-485 to Ethernet converter / Wi-Fi

Code: D80011.

Dimensions Connections



