



## CMBUS-8

CMBUS-8, M-Bus to Modbus-RTU Converter,

Code: D80208.

### Description

M-Bus to Modbus physical media conversion gateway, allowing integration of M-Bus interface meters into Modbus RTU networks. Its compact DIN rail design (1 module) ensures easy installation and adaptability to multiple environments. It offers features such as:

- M-Bus to Modbus communication.
- Operates as a Modbus slave with a unique identifier on the network.
- Compact and robust design.
- Compatible with most standard M-Bus meters.

### Application

Thanks to its direct M-Bus to Modbus conversion, CMBUS gateways are ideal for integration and monitoring projects requiring the centralisation of data from M-Bus meters in Modbus systems. Typical applications include:

- Integration of energy, water, or gas meters into Modbus systems or SCADA platforms.
- Rebilling of consumption in office buildings, shopping centres, hotels, or multi-user spaces.
- Energy monitoring in industrial or service installations with multiple M-Bus meters.
- Automation of water, HVAC, or lighting infrastructures via PLC or BMS integration.



# CMBUS-8

M-Bus to Modbus RTU conversion gateway

Code: D80208.

## Specifications

### DC power supply

Consumption	55 mA
Nominal voltage	18 ... 30 Vdc

### Mechanical characteristics

Size (mm) width x height x depth	17.5 x 90 x 58 (mm)
Weight (kg)	0,065

### Communication Network

Protocol	Modbus RTU / M-BUS
Technology / Interface	M-BUS

### CMBUS M-Bus to Modbus Converter

CODE	TYPE	Description
<b>M-Bus</b>		
D80208.	CMBUS-8	M-Bus to Modbus-RTU Converter, up to 8 Mbus slaves




## CMBUS-8

M-Bus to Modbus RTU conversion gateway

Code: D80208.

### Dimensions



### Connections

