



CMBUS-8

CMBUS-8, M-Bus to Modbus Converter,

Code: D80208.

Description

CMBUS protocol transducers enable devices with RS-485 Modbus Master communications to communicate with different M-BUS slave units.

There are two unit models:

- The CMBUS-8 model can communicate with 8 slave units (100 parameters).
- $\circ~$ The $\mbox{CMBUS-24}$ model can communicate with 24 slave units (500 parameters)

Application

In Northern and Central European installations there are many devices that log consumption, equipped with M-BUS communications protocols or interfaces. These equipments measure cold and hot water consumption, as well steam, gas, electricity, etc. Said equipments deliver characteristic parameters of the systems they control, such as, water temperature, volume, flow, pressure or electrical energy consumption, as well as the more basic parameters of an electrical network. The M-BUS (BUS-Meter) protocol is a communications system for reading energy meters that has been designed to automate data collection by remote control or computer programs.







CMBUS-8

M-Bus to Modbus Converter

Code: D80208.

Specifications

DC power supply		
Consumption	55 mA	
Nominal voltage	18 30 Vdc	
Mechanical characteristics		
Size (mm) width x height x depth	17.5 x 90 x 58 (mm)	
Weight (kg)	0,065	
Communication Network		
Protocol	Modbus RTU / M-BUS	
Technology / Type	M-BUS	

CMBUS

M-Bus to Modbus Converter

CODE	TYPE	Description
M-BUS		
D80208.	CMBUS-8	M-Bus to Modbus Converter, up to 8 Mbus slaves







CMBUS-8

M-Bus to Modbus Converter

Code: D80208.

Connections Dimensions





