



## STM-S

---

STM-S, Module with 4 measurement outputs,

Code: E82S00. (CONSULTAR DISPONIBILIDAD)

### Description

---

**STM** is smart analyser that supports up to 32 channels. Designed specifically to supervise photovoltaic strings, the **STM** allows for the maximum performance of the photovoltaic array thanks to its high measuring accuracy.

The solution consists of different modules:

**STM-C**: Smart module that is able to calculate powers, compare string performances, detect reverse currents, etc. It also features:

- One 1,500 VDC input
- Four voltage-free digital inputs
- One analogue input 0/4...20 mA
- One input for Pt100 or Pt1000
- A LoRa wireless communications module

**STM-S**: Current measurement module with 4 measurement channels of up to 42 A each. Up to 8

**STM-S** modules can be connected to obtain 32 channels.

Its modularity, flexibility of installation, smart characteristics and robustness make the **STM** the perfect piece of equipment to supervise the correct operation of the photovoltaic array.

### Application

---

Supervision of photovoltaic strings in solar farms and self-consumption installations



## STM-S

---

Analyser for photovoltaic strings

Code: E82S00.

## Specifications

---

### Mechanical characteristics

---

Size (mm) width x height x depth

80 x 127.8 x 72.35 (mm)

---

The minimum configuration of the STM solution is made up of an STM-C module and an STM-S module



## STM-S

---

Analyser for photovoltaic strings

Code: E82S00.

### Dimensions

---



### Connections

---

