



# FP KIT GW LoRa-ETH F915

KIT GW LoRa-ETH-F915, Gateway LoRa-Ethernet communications kit 915 MHz, structure + base + anchors for mounting included,

Code: E83G020021200    **DESCATALOGADO**

## Specifications

### DC power supply

Installation category	CAT II 1500 V
Consumption	3.6 W
Nominal voltage	24 V $\pm$ 10%

### Environmental characteristics

Protection class	IP 00
Relative humidity (without condensation)	5 ... 95 %
Installation, location, position.	3000 m
Storage temperature	-25...+80 °C
Working temperature	-25...+70 °C

### Mechanical characteristics

Envelope	Self-extinguishing V0 plastic
Fastening	DIN rail
Weight (kg)	14,46

### Current measurement circuit

Installation category	CAT II 1500 V
Impedance	0.5 m $\Omega$
Minimum current measurement	0.1 A

### Voltage measurement circuit

Installation category	CAT II 1500 V
Input impedance	2400 k $\Omega$
Voltage measuring range	-25 ... -1500 Vdc
Maximum input voltage consumption	0,625 mA
Minimum measurement voltage (Vstart)	-25 V

### Input

Accuracy	$\pm$ 3°C
Range	-30 ... 100°C
Resolution	$\pm$ 0,1 mA
Type	Pt100/1000

### Standards

Electrical safety, Maximum height (m)	3000
Electrical safety, Installation category	Protection against electric shock: Double class II insulation



# FP KIT GW LoRa-ETH F915

Code: E83G020021200

Standards		EN 61000-6-2, EN 61000-6-4, EN 61010-1, EN 61010-2-30
User interface		
LED		4
Digital inputs		
Input/output insulation		Optoisolated
Quantity		3
Type		Potential free contact
Maximum short-circuit current		3.2 mA
Maximum open circuit voltage		24 V

The minimum configuration of the STM solution is made up of an STM-C module and an STM-S module