

STM-S-12-485

Code: E85SC1. DESCATALOGADO

- > Protocol: Modbus-RTU
- > Communications: RS-485
- > Digital inputs: 3
- > Measure: 45 A
- > Power supply (Vac): 24 Vdc
- > Mounting: DIN rail

#### Application

Supervision of photovoltaic strings in solar farms and self-consumption installations

# Circutor



Analyser for photovoltaic strings

Code: E85SC1.

#### Specifications

DC power supply	
Installation category	CAT II 1500 V
Consumption	3.6 W
Nominal voltage	24 Vdc ± 10 %
Mechanical characteristics	
Size (mm) width x height x depth	337.5 x 114 x 58 (mm)
Envelope	Self-extinguishing VO plastic
Fastening	DIN rail
Weight (kg)	0,52
Environmental characteristics	
Protection class	IP 00
Relative humidity (without condensation)	5 95 %
Installation, location, position.	3000 m
Storage temperature	-25+80 °C
Working temperature	-25+70 °C
Current measurement circuit	
Installation category	CAT II 1500 V
Consumption	1 Chanel: 1.0125 W
Impedance	0.5 mΩ
Phase current measuring range	0.1 45 A DC
Minimum current measurement	0.1 A
/oltage measurement circuit	
Installation category	CAT II 1500 V
Input impedance	2400 kΩ
Voltage measuring range	-251500 Vdc
Maximum input voltage consumption	0,625 mA
Minimum measurement voltage (Vstart)	-25 V
Input	
Accuracy	± 3°C
Range	-30 100°C
Resolution	±0,1 mA
Туре	Pt100/1000





Analyser for photovoltaic strings

Code: E85SC1.

3000
Protection against electric shock: Double class II insulation
EN 61000-6-2, EN 61000-6-4, EN 61010-1, EN 61010-2-30
4
Optoisolated
3
Potential free contact
3.2 mA
24 V

The minimum configuration of the STM solution is made up of an STM-C module and an STM-S module  $% \mathcal{M} = \mathcal{M} = \mathcal{M} + \mathcal{M} +$ 

# Circutor



Analyser for photovoltaic strings

Code: E85SC1.

# Dimensions

# Connections

×

×

