

STM-S-24-485

STM-S-24-485

Code: E85SE1. DESCATALOGADO

- > Protocol: Modbus-RTU
- > Communications: RS-485
- > Digital inputs: 3
- > Measure: 30 A
- > Power supply (Vac): 24 Vdc
- > Mounting: DIN rail

Application

Supervision of photovoltaic strings in solar farms and self-consumption installations

Circutor

Page 2 of 4



STM-S-24-485

Analyser for photovoltaic strings

Code: E85SE1.

Specifications

| DC power supply | | |
|--|-------------------------------|--|
| Installation category | CAT II 1500 V | |
| Consumption | 3.6 W | |
| Nominal voltage | 24 V ±10% | |
| Aechanical characteristics | | |
| Size (mm) width x height x depth | 337.5 x 114 x 94.5 (mm) | |
| Envelope | Self-extinguishing V0 plastic | |
| Fastening | DIN rail | |
| Weight (kg) | 0,82 | |
| Invironmental characteristics | | |
| Protection class | IP 00 | |
| Relative humidity (without condensation) | 5 95 % | |
| Installation, location, position. | 3000 m | |
| Storage temperature | -25+80 °C | |
| Working temperature | -25+70 °C | |
| Current measurement circuit | | |
| Installation category | CAT II 1500 V | |
| Consumption | 1 Chanel: 1.0125 W | |
| Impedance | 0.5 mΩ | |
| Phase current measuring range | 0.1 30 A DC | |
| Minimum current measurement | 0.1 A | |
| /oltage measurement circuit | | |
| Installation category | CAT II 1500 V | |
| Input impedance | 2400 kΩ | |
| Voltage measuring range | -251500 Vdc | |
| Maximum input voltage consumption | 0,625 mA | |
| Minimum measurement voltage (Vstart) | -25 V | |
| nput | | |
| Accuracy | ± 3°C | |
| Range | -30 100°C | |
| Resolution | ±0,1 mA | |
| Туре | Pt100/1000 | |





STM-S-24-485

Analyser for photovoltaic strings

Code: E85SE1.

| Standards | | |
|--|---|--|
| Electrical safety, Maximum height (m) | 3000 | |
| Electrical safety, Installation category | Protection against electric shock: Double class II insulation | |
| Standards | EN 61000-6-2, EN 61000-6-4, EN 61010-1, EN 61010-2-30 | |
| User interface | | |
| LED | 4 | |
| Digital inputs | | |
| Input/output insulation | Optoisolated | |
| Quantity | 3 | |
| Туре | Potential free contact | |
| Maximum short-circuit current | 3.2 mA | |
| Maximum open circuit voltage | 24 V | |

The minimum configuration of the STM solution is made up of an STM-C module and an STM-S module $% \mathcal{M} = \mathcal{M} = \mathcal{M} + \mathcal{M} +$

Circutor



STM-S-24-485

Analyser for photovoltaic strings

Code: E85SE1.

Dimensions

Connections

×

×

