



PVT2

PVT2, simple canopy,

Code: EPVT20.

Description

The PVT series consists of 3 models: PVT2, PVT2 -INV and PVT4. It is ideal for large covered parking areas with photovoltaic solar production. The main structure of the PVT model is made up of standardised IPE profiles that will allow us to carry out much larger projects, with lower costs and delivery times and to better adapt to the requirements of the terrain.

Application

- Photovoltaic energy installations in buildings in which the roof is not suitable for the installation of conventional photovoltaic panels.
- Instantaneous self-consumption, ideal for industrial, commercial or residential buildings with outdoor parking and daytime consumption.



PVT2

Solar canopies for large projects

Code: EPVT20.

Specifications

Características Pie

Grado protección	C4
Material	ACERO S-275 JR
Medidas	1850 x 2640 x 330 mm
Peso	127 kg
Separación pies	7,5 m

Características Vela

Grado inclinación	9°
Grado protección	C4
Material	ACERO S-275 JR
Medidas	180 x 4675 x 91 mm
Peso	75 kg

Features / performance

Additional	Waterproof Mounting service Inverted roof possible Focused on large projects Possibility of linear spaces
Optional	Degree of protection C5

Standards

Standards	European: Eurocode: 0, 1 and 3 Spanish: CÓDIGO TÉCNICO DE LA EDIFICACION: DB-SE-SE, DB-SE-AE, DB-SE-A.
-----------	--

PVT

Solar canopies for instant self-consumption

CODE	TYPE	Description
EPVT10.	PVT2-INV	Simple canopy with inverted roof
EPVT20.	PVT2	simple canopy
EPVK40.	PVT4	Double canopy for two facing rows of cars

The PVM canopy references include the following components:

HalfCell monocrystalline modules (120)
 PVM2, PVM4 type canopy structure
 PV inverter/s
 StringBox
 CombinerBox
 Environmental sensors (radiation and plate/ambient temperature)

It includes the price of the template and the RAL paint at the customer's request.
 DELIVERY NOT INCLUDED



PVT2

Solar canopies for large projects

Code: EPVT20.

Dimensions

