



EC144 300mA

EC144 300mA, Milliammeter

Code: M10145.

- > Scale: 90°, P2
- > Accuracy: 1,5
- > Measurement Range (A): 0,3
- > Modules: 144x144

Description

- No auxiliary power needed, only type CEC 96.
- DIN boxes, sizes 48, 72, 96 and 144.
- Accuracy class 1.5
- True root mean square value of 100 mA... 100 A
- Interchangeable scales for EC 48, EC 72, EC 96, EM 45, EC 72 FA, EC 96 FA
- Fully adjustable alarm system for CEC 96

Application

Alternating current applications to quickly and visually monitor the status of the current.



EC144 300mA

Moving-iron ammeters (AC)

Code: M10145.

Specifications

Mechanical characteristics

| | |
|----------------------------------|-----------------------|
| Size (mm) width x height x depth | 144 x 144 x 71.8 (mm) |
| Fastening | Panel |
| Weight (kg) | 0,43 |

Environmental characteristics

| | |
|---------------------|---|
| Protection class | Panel: IP 52 (Front), IP 00 (Terminals) |
| Storage temperature | -25...+40 °C |
| Working temperature | +10 ... +30 °C |

Standards

| | |
|---------------------------------------|--|
| Certifications | CE, UL |
| Electrical safety, Maximum height (m) | 2000 |
| Standards | BS 89, UNE-EN 60051, IEC 144, UL94, DIN 43780, IEC 51, UNE 21318 |

Current measurement circuit

| | |
|--------------------|--|
| Consumption | 0,3 ... 1,5 VA |
| Sampling frequency | 20...100 Hz |
| Allowable overload | 1,2 In permanent / 5 In during 30s / 10 In during 5s / 40 In during 1s |

Electrical characteristics

| | |
|-----------------------------|---|
| Insulation voltage, circuit | 2 KV, 50 HZ <1 min entre mecanismo y caja |
|-----------------------------|---|

Measurement accuracy

| | |
|----------|----------|
| Accuracy | 1,5 % FE |
|----------|----------|

EC-mA

Moving Iron Milliampmeters

| CODE | TYPE | Scale | Accuracy | Measurement Range (A) | Modules |
|---------|------------|---------|----------|-----------------------|---------|
| M10111. | EC48 100mA | 90°, P2 | 1,5 | 0,1 | 48x48 |
| M10112. | EC48 150mA | 90°, P2 | 1,5 | 0,15 | 48x48 |
| M10114. | EC48 250mA | 90°, P2 | 1,5 | 0,25 | 48x48 |
| M10115. | EC48 300mA | 90°, P2 | 1,5 | 0,3 | 48x48 |
| M10116. | EC48 400mA | 90°, P2 | 1,5 | 0,4 | 48x48 |
| M10117. | EC48 500mA | 90°, P2 | 1,5 | 0,5 | 48x48 |
| M10118. | EC48 600mA | 90°, P2 | 1,5 | 0,6 | 48x48 |
| M10121. | EC72 100mA | 90°, P2 | 1,5 | 0,1 | 72x72 |



EC144 300mA

Moving-iron ammeters (AC)

Code: M10145.

| CODE | TYPE | Scale | Accuracy | Measurement Range (A) | Modules |
|---------|-------------|---------|----------|-----------------------|---------|
| M10122. | EC72 150mA | 90°, P2 | 1,5 | 0,15 | 72x72 |
| M10124. | EC72 250mA | 90°, P2 | 1,5 | 0,25 | 72x72 |
| M10125. | EC72 300mA | 90°, P2 | 1,5 | 0,3 | 72x72 |
| M10126. | EC72 400mA | 90°, P2 | 1,5 | 0,4 | 72x72 |
| M10127. | EC72 500mA | 90°, P2 | 1,5 | 0,5 | 72x72 |
| M10128. | EC72 600mA | 90°, P2 | 1,5 | 0,6 | 72x72 |
| M10131. | EC96 100mA | 90°, P2 | 1,5 | 0,1 | 96x96 |
| M10132. | EC96 150mA | 90°, P2 | 1,5 | 0,15 | 96x96 |
| M10134. | EC96 250mA | 90°, P2 | 1,5 | 0,25 | 96x96 |
| M10135. | EC96 300mA | 90°, P2 | 1,5 | 0,3 | 96x96 |
| M10136. | EC96 400mA | 90°, P2 | 1,5 | 0,4 | 96x96 |
| M10137. | EC96 500mA | 90°, P2 | 1,5 | 0,5 | 96x96 |
| M10138. | EC96 600mA | 90°, P2 | 1,5 | 0,6 | 96x96 |
| M10141. | EC144 100mA | 90°, P2 | 1,5 | 0,1 | 144x144 |
| M10142. | EC144 150mA | 90°, P2 | 1,5 | 0,15 | 144x144 |
| M10144. | EC144 250mA | 90°, P2 | 1,5 | 0,25 | 144x144 |
| M10145. | EC144 300mA | 90°, P2 | 1,5 | 0,3 | 144x144 |
| M10146. | EC144 400mA | 90°, P2 | 1,5 | 0,4 | 144x144 |
| M10147. | EC144 500mA | 90°, P2 | 1,5 | 0,5 | 144x144 |
| M10148. | EC144 600mA | 90°, P2 | 1,5 | 0,6 | 144x144 |



EC144 300mA

Moving-iron ammeters (AC)

Code: M10145.

Dimensions



Connections

