



EC48 600V

EC48 600V, Voltmeter

Code: M10419.

- > Scale: 90°, P1
- > Accuracy: 1,5
- > Measurement Range (V): 600
- > Modules: 48x48

Description

- No need for auxiliary power supply, only the CEC 96 type
- DIN boxes with dimensions: 48, 72, 96 and 144
- Measurement in true root mean square or V ... 600 V ac
- Exchangeable scales for EC48, EC72, EC96, EM 45
- The alarm system can be fully configured for CEC 96

&nb

Application

In alternating current applications, to control the state of the voltage quickly and visually.



EC48 600V

Moving Iron Voltmeters

Code: M10419.

Specifications

Mechanical characteristics

Size (mm) width x height x depth	48 x 48 x 66.2 (mm)
Fastening	Panel
Weight (kg)	0,085

Environmental characteristics

Protection class	Panel: IP 52 (Front), IP 20 (Terminals)
Storage temperature	-25...+40 °C
Working temperature	+10 ... +30 °C

Standards

Certifications	CE
Electrical safety, Maximum height (m)	2000
Standards	BS 89, UNE-EN 60051, IEC 144, DIN 43780, IEC 51, UNE 21318

Voltage measurement circuit

Consumption	1 ... 4 VA
Sampling frequency	20 ... 100 Hz
Maximum permanent measurement voltage	1,5 Vn permanent rated voltage / 2 Vn during 5s

Electrical characteristics

Insulation voltage, circuit	2 kV, 50 Hz, 1 min entre mecanismo y caja
-----------------------------	---

Measurement accuracy

Accuracy	1,5 % FE
----------	----------

EC-V

Moving Iron Voltmeters (ac)

CODE	TYPE	Scale	Accuracy	Modules
M10415.	EC48 250V	90°, P1	1,5	48x48
M10416.	EC48 300V	90°, P1	1,5	48x48
M10417.	EC48 400V	90°, P1	1,5	48x48
M10418.	EC48 500V	90°, P1	1,5	48x48
M10419.	EC48 600V	90°, P1	1,5	48x48
M10410.	EC48 .../110V	90°, P1	1,5	48x48
M10425.	EC72 250V	90°, P1	1,5	72x72
M10426.	EC72 300V	90°, P1	1,5	72x72



EC48 600V

Moving Iron Voltmeters

Code: M10419.

CODE	TYPE	Scale	Accuracy	Modules
M10427.	EC72 400V	90°, P1	1,5	72x72
M10428.	EC72 500V	90°, P1	1,5	72x72
M10429.	EC72 600V	90°, P1	1,5	72x72
M10420.	EC72 .../110V	90°, P1	1,5	72x72
M10435.	EC96 250V	90°, P1	1,5	96x96
M10436.	EC96 300V	90°, P1	1,5	96x96
M10437.	EC96 400V	90°, P1	1,5	96x96
M10438.	EC96 500V	90°, P1	1,5	96x96
M10439.	EC96 600V	90°, P1	1,5	96x96
M10430.	EC96 .../110V	90°, P1	1,5	96x96

Exchangeable scales, Voltmeters 90°




EC48 600V

Moving Iron Voltmeters

Code: M10419.

Dimensions

Connections



Type	Fig. EC	Fig. BC	a	b	c	d	e
48	1-3	1-3	48	44,7	61	5,2	45
72	1-3-4	2-3-4	72	67,2	43,5	5,7	68
96	1-3-4	2-3-4	96	91	43,5	5,7	92
144	2-3-4	2-3-4	144	137	64,5	7,3	138

