

Page 1 of 3





## EMSC45 .../110V

EMSC45 .../110V, oltmeter

Code: M10470. (CONSULTAR DISPONIBILIDAD)

> Scale: 90° P1 > Accuracy: 1,5

> Measurement Range (V): .../110

### Description

- $\circ\ \ \mbox{No need for auxiliary power supply}$
- $\circ~$  Measurement in true root mean square or V ... 600 V ac
- o Exchangeable scales

#### **Application**

In alternating current applications, to control the state of the voltage quickly and visually.







## EMSC45 .../110V

Moving Iron Voltmeters

Code: M10470.

### **Specifications**

Size (mm) width x height x depth	85 x 52 x 65 (mm)
	0,142
Weight (kg)	U,14Z
Environmental characteristics	
Protection class	DIN rail: IP 52 (front), IP 00 (terminals)
Storage temperature	-25+40 °C
Working temperature	+10 +30 °C
Standards	
Certifications	CE
Electrical safety, Maximum height (m)	2000
Standards	BS 89, UNE-EN 60051, IEC 144, DIN 43780, IEC 51, UNE 21318
Voltage measurement circuit	
Consumption	1 4 VA
Sampling frequency	20 100 Hz
Maximum permanent measurement voltage	1,5 Vn permanent rated voltage / 2 Vn during 5s
Electrical characteristics	
Insulation voltage, circuit	2 kV, 50 Hz, 1 min entre mecanismo y caja
Measurement accuracy	
Accuracy	1,5 % FE



Exchangeable scales, Voltmeters 90°







# EMSC45 .../110V

Moving Iron Voltmeters

Code: M10470.

# Connections



