

# EC96 F III+N 400V

EC96 F III+N 400V, Voltmeter

Code: M10737.

> Scale: 90°, P1
> System: Three-phase 4 wire
> Accuracy: 1,5
> Measurement Range (V): 400
> Modules: 96x96

## Specifications

### Mechanical characteristics

| | |
|---|---|
| Size (mm) width x height x depth | 96 x 96 x 49.2 (mm) |
| Fastening | Panel |
| Weight (kg) | 0,22 |

### Environmental characteristics

| | |
|---|---|
| Protection class | Panel: IP 52 (Front), IP 00 (Terminals) |
| Storage temperature | -25...+40 °C |
| Working temperature | +10 ... +30 °C |

### Standards

| | |
|---|---|
| Certifications | CE |
| Electrical safety, Maximum height (m) | 2000 |
| Standards | BS 89, UNE-EN 60051, IEC 144, DIN 43780, IEC 51, UNE 21318 |

### Voltage measurement circuit

| | |
|---|---|
| Consumption | 1 ... 4 VA |
| Sampling frequency | 20 ... 100 Hz |
| Maximum permanent measurement voltage | 1,5 Vn permanent rated voltage / 2 Vn during 5s |

### Electrical characteristics

| | |
|---|---|
| Insulation voltage, circuit | 2 kV, 50 Hz, 1 min entre mecanismo y caja |

### Measurement accuracy

| | |
|---|---|
| Accuracy | 1,5 % FE |

EC-F-V
Voltmeters with phase switch for AC measurement

| CODE | TYPE | Scale | Accuracy | Modules |
|---|---|---|---|---|
| **Three-phase 3 wire** | | | | |
| M10625. | EC72 FIII 250V | 90°, P1 | 1,5 | 72x72 |
| M10626. | EC72 FIII 300V | 90°, P1 | 1,5 | 72x72 |



# EC96 F III+N 400V

Code: M10737.

| CODE | TYPE | Scale | Accuracy | Modules |
|---|---|---|---|---|
| M10627. | EC72 FIII 400V | 90°, P1 | 1,5 | 72x72 |
| M10628. | EC72 FIII 500V | 90°, P1 | 1,5 | 72x72 |
| M10629. | EC72 FIII 600V | 90°, P1 | 1,5 | 72x72 |
| M10632. | EC96 FIII .../110V | 90°, P1 | 1,5 | 72x72 |
| M10635. | EC96 FIII 250V | 90°, P1 | 1,5 | 96x96 |
| M10636. | EC96 FIII 300V | 90°, P1 | 1,5 | 96x96 |
| M10637. | EC96 FIII 400V | 90°, P1 | 1,5 | 96x96 |
| M10638. | EC96 FIII 500V | 90°, P1 | 1,5 | 96x96 |
| M10639. | EC96 FIII 600V | 90°, P1 | 1,5 | 96x96 |
| **Three-phase 4 wire** | | | | |
| M10725. | EC72 F III+N 250V | 90°, P1 | 1,5 | 72x72 |
| M10726. | EC72 F III+N 300V | 90°, P1 | 1,5 | 72x72 |
| M10727. | EC72 F III+N 400V | 90°, P1 | 1,5 | 72x72 |
| M10728. | EC72 F III+N 500V | 90°, P1 | 1,5 | 72x72 |
| M10729. | EC72 F III+N 600V | 90°, P1 | 1,5 | 72x72 |
| M10735. | EC96 F III+N 250V | 90°, P1 | 1,5 | 96x96 |
| M10736. | EC96 F III+N 300V | 90°, P1 | 1,5 | 96x96 |
| M10737. | EC96 F III+N 400V | 90°, P1 | 1,5 | 96x96 |
| M10738. | EC96 F III+N 500V | 90°, P1 | 1,5 | 96x96 |
| M10739. | EC96 F III+N 600V | 90°, P1 | 1,5 | 96x96 |


Creation date: 25/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



# EC96 F III+N 400V

Code: M10737.

## Dimensions




| Tipo | a | b | c | d | e |
|---|---|---|---|---|---|
| 72 | 72 | 67,2 | 43,5 | 5,7 | 68 +0,8 |
| 96 | 96 | 91 | 43,5 | 5,7 | 92 +0,8 |

## Connections

