

EZC72 .../5A

EZC72 .../5A, Ammeter

Code: M10920.

- > Scale: 240°, P2
- > Accuracy: 1,5
- > Measurement Range (A): .../5 A
- > Modules: 72x72

Specifications

Mechanical characteristics

Size (mm) width x height x depth	72 x 72 x 49.2 (mm)
Fastening	Panel
Weight (kg)	0,17

Environmental characteristics

Protection class	Panel: IP 52 (Front), IP 00 (Terminals)
Storage temperature	-25...+40 °C
Working temperature	+10 ... +30 °C

Standards

Certifications	CE, UL
Electrical safety, Maximum height (m)	2000
Standards	BS 89, UNE-EN 60051, IEC 144, UL94, DIN 43780, IEC 51, UNE 21318

Current measurement circuit

Consumption	0,3 ... 1,5 VA
Sampling frequency	20...100 Hz
Allowable overload	1,2 In permanent / 5 In during 30s / 10 In during 5s / 40 In during 1s

Electrical characteristics

Insulation voltage, circuit	2 KV, 50 HZ <1 min entre mecanismo y caja
-----------------------------	---

Measurement accuracy


Accuracy	1,5 % FE
----------	----------

EZC-A

Moving Iron Ammeter (ac) 240 °

CODE	TYPE	Scale	Accuracy	Measurement Range (A)	Modules
M10920.	EZC72 .../5A	240°, P2	5	.../5 A	72x72
M10930.	EZC96 .../5A	240°, P2	5	.../5 A	96x96

Exchangeable scales. See next page Indicate transformer ratio



EZC72 .../5A

Code: M10920.

Dimensions

