



## BC72 10A

---

BC72 10A, Ammeter

Code: M11423.

- > Scale: 90°, P1
- > Accuracy: 1,5
- > Measurement Range (A): 10
- > Device: BC72
- > Modules: 72x72

### Description

---

- No need for auxiliary power supply, only the CEC 96 type
- DIN boxes with dimensions: 48, 72, 96 and 144
- Precision class 1.5
- Measurement in DC 25  $\mu$ A ... 60 A, or ... 60 mV
- Exchangeable scales for BC48, BC72, BC96
- The alarm system can be fully configured for CBC 96

### Application

---

In direct current applications, to control the state of the current quickly and visually.



## BC72 10A

Moving coil ammeters

Code: M11423.

### Specifications

#### Mechanical characteristics

Size (mm) width x height x depth	72 x 72 x 49.2 (mm)
Fastening	Panel
Weight (kg)	0,17

#### Environmental characteristics

Protection class	Panel: IP 52 (Front), IP 00 (Terminals)
Storage temperature	-25...+40 °C
Working temperature	+10 ... +30 °C

#### Standards

Certifications	CE
Electrical safety, Maximum height (m)	2000
Standards	BS 89, UNE-EN 60051, IEC 144, DIN 43780, IEC 51, UNE 21318

#### Current measurement circuit

Consumption	60 mV
Allowable overload	1,2 In permanent / 5 In during 30s / 10 In during 5s / 40 In during 1s

#### Electrical characteristics

Insulation voltage, circuit	2 kV a 50Hz < 1 min entre mecanismo y caja
-----------------------------	--

#### Measurement accuracy

Accuracy	1,5 % FE
----------	----------

#### BC-A

Moving coil ammeters (dc)

CODE	TYPE	Scale	Accuracy	Measurement Range (A)	Modules	Device
M11412.	BC48 5A	90° , P1	1,5	5	48x48	BC48
M11413.	BC48 10A	90° , P1	1,5	10	48x48	BC48
M11416.	BC48 25A	90° , P1	1,5	25	48x48	BC48
M11419.	BC48 50A	90° , P1	1,5	50	48x48	BC48
M11410.	BC48 .../60mV	90° , P1	1,5	.../60mV	48x48	BC48
M11422.	BC72 5A	90° , P1	1,5	5	72x72	BC72
M11423.	BC72 10A	90° , P1	1,5	10	72x72	BC72
M11426.	BC72 25A	90° , P1	1,5	25	72x72	BC72



## BC72 10A

Moving coil ammeters

Code: M11423.

CODE	TYPE	Scale	Accuracy	Measurement Range (A)	Modules	Device
M11429.	BC72 50A	90° , P1	1,5	50	72x72	BC72
M1142A.	BC72 60A	90° , P1	1,5	60	72x72	BC72
M11420.	BC72 .../60mV	90° , P1	1,5	.../60mV	72x72	BC72
M11432.	BC96 5A	90° , P1	1,5	5	96x96	BC96
M11433.	BC96 10A	90° , P1	1,5	10	96x96	BC96
M11436.	BC96 25A	90° , P1	1,5	25	96x96	BC96
M11439.	BC96 50A	90° , P1	1,5	50	96x96	BC96
M1143A.	BC96 60A	90° , P1	1,5	60	96x96	BC96
M11430.	BC96 .../60mV	90° , P1	1,5	.../60mV	96x96	BC96

Exchangeable scales. External shunts, see section Measuring current transformers and shunts



## BC72 10A

Moving coil ammeters

Code: M11423.

### Connections

