



BMSC45 30V

BMSC45 30V, Voltmeter

Code: M11765. DESCATALOGADO

- > Scale: 90°, P1
- > Accuracy: 1,5
- > Measurement Range (V): 30
- > Device: BMSC45

Description

- No need for auxiliary power supply,
- Precision class 1.5
- Measurement in DC 25 uA ... 60 A, or ... 60 mV
- Exchangeable scales

Application

In direct current applications, to control the state of the current quickly and visually.



BMSC45 30V

Moving coil voltmeters

Code: M11765.

Specifications

Mechanical characteristics

Size (mm) width x height x depth	85 x 65 x 52 (mm)
Fastening	DIN rail
Weight (kg)	0,11

Environmental characteristics

Protection class	DIN rail: IP 52 (front), IP 00 (terminals)
Storage temperature	-25...+40 °C
Working temperature	+10 ... +30 °C

Standards

Certifications	CE
Electrical safety, Maximum height (m)	2000
Standards	BS 89, UNE-EN 60051, IEC 144, DIN 43780, IEC 51, UNE 21318

Voltage measurement circuit

Consumption	1000 Ω/V
Sampling frequency	20 ... 100 Hz
Maximum permanent measurement voltage	1,2 Vn / 2 Vn during 5s

Electrical characteristics

Insulation voltage, circuit	2 kV a 50Hz < 1 min entre mecanismo y caja
-----------------------------	--

Measurement accuracy

Accuracy	1,5 % FE
----------	----------



BMSC45 30V

Moving coil voltmeters

Code: M11765.

Dimensions



Connections

