

BMSC45 600V

BMSC45 600V, Voltmeter

| Code: M1176F. DESCA | TALOGADO |
|---------------------|----------|
|---------------------|----------|

- > Scale: 90° , P1
- > Accuracy: 1,5
- > Measurement Range (V): 600
- > Device: BMSC45

Description

- No need for auxiliary power supply,
- Precision class 1.5
- Measurement in DC 25 uA ... 60 A, or ... 60 mV
- $\circ~$ Exchangeable scales

Application

In direct current applications, to control the state of the current quickly and visually.

Circutor



BMSC45 600V

Moving coil voltmeters

Code: M1176F.

Specifications

| Size (mm) width x height x depth | 85 x 65 x 52 (mm) |
|---------------------------------------|--|
| Fastening | DIN rail |
| Weight (kg) | 0,15 |
| invironmental characteristics | |
| Protection class | DIN rail: IP 52 (front), IP 00 (terminals) |
| Storage temperature | -25+40 °C |
| Working temperature | +10 +30 °C |
| itandards | |
| Certifications | CE |
| Electrical safety, Maximum height (m) | 2000 |
| Standards | BS 89, UNE-EN 60051, IEC 144, DIN 43780, IEC 51, UNE 21318 |
| /oltage measurement circuit | |
| Consumption | 1000 Ω/V |
| Sampling frequency | 20 100 Hz |
| Maximum permanent measurement voltage | 1,2 Vn / 2 Vn during 5s |
| Electrical characteristics | |
| Insulation voltage, circuit | 2 kV a 50Hz < 1 min entre mecanismo y caja |
| Measurement accuracy | |
| Accuracy | 1,5 % FE |





BMSC45 600V

Moving coil voltmeters

Code: M1176F.

Dimensions

Connections

×

×

