

#### MC96 .../5 A

MC96 .../5 A, Maximeter

Code: M	12231.
---------	--------

> Scale: 90°, P1, 2

- > Accuracy: 3
- > Measurement Range (A): .../5 A
- > Modules: 96x96

#### Specifications

Mechanical characteristics	
Size (mm) width x height x depth	96 x 96 x 49.2 (mm)
Fastening	Panel
Weight (kg)	0,14
Environmental characteristics	
Protection class	Panel: IP 52 (Front), IP 00 (Terminals)
Storage temperature	-25+40 °C
Working temperature	+10 +30 °C
Standards	
Certifications	CE
Electrical safety, Maximum height (m)	2000
Standards	BS 89, UNE-EN 60051, IEC 144, DIN 43780, IEC 51, UNE 21318
Current measurement circuit	
Consumption	3,25 VA
Allowable overload	1,5 In permanent / 15 In during 1s
Electrical characteristics	
Insulation voltage, circuit	2 KV A 50 HZ < 1min entre mecanismo y caja
Measurement accuracy	
Accuracy	± 3 % FE

#### MC

Maximeter ammeters

CODE	ТҮРЕ	Scale	Accuracy	Measurement Range (A)	Modules		
M12211.	MC48/5 A	90°, P1, 2	3	/5 A	48x48		
M12221.	MC72/5A	90°, P1, 2	3	/5 A	72x72		
M15521.	MC72 / 5A 120%	90°, P1, 2	3	/5 A	72x72		
M12231.	MC96/5 A	90°, P1, 2	3	/5 A	96x96		
M15531.	MC96/5A 120%	90°, P1, 2	3	/5 A	96x96		





## MC96 .../5 A

Code: M12231.

CODE	ТҮРЕ	Scale	Accuracy	Measurement Range (A)	Modules
M12241.	MC144/5A	90°, P1, 2	3	/5 A	144x144

Scale NOT included

Circutor



## MC96 .../5 A

Code: M12231.

### Connections

×

# Circutor