



ZC48 0...10V

ZC 48

Code: M12513. DESCATALOGADO

- > 0 ... 10V
- > Process indicator

Description

- Does not need an auxiliary power supply.
- DIN boxes with dimensions 48, 72, 96 and 144 mm.
- Precision class 1,5
- Measurement in D.C. of 0 ... 10 V, 0/4 ... 20 mA, .../60 mV
- Exchangeable scales for BC48, BC72, BC96, BM 45

Application

For the measurement of the mean value of voltages and currents in direct current circuits, even of the pulsating type, in a vast margin of values.



ZC48 0...10V

Process indicator

Code: M12513.

Specifications

Mechanical characteristics

| | |
|----------------------------------|---------------------|
| Size (mm) width x height x depth | 48 x 48 x 66.2 (mm) |
| Fastening | Panel |
| Weight (kg) | 0,075 |

ZC

Process indicators, 240°

| CODE | TYPE | Scale | Accuracy | Modules | Full scale |
|---------|---------------|---------|----------|---------|------------|
| M12523. | ZC72 0...10V | 240° P1 | 1,5 | 72x72 | 0...10 V |
| M12521. | ZC72 4...20mA | 240° P1 | 1,5 | 72x72 | 4...20 mA |

Scales included in the price (*) The 6-digit code includes the 4 ... 20 mA scale