Page 1 of 2





ZC48 0...10V

ZC 48

Code: M12513. DESCATALOGADO

> 0 ... 10V

> Process indicator

Description

- o Does not need an auxiliary power supply.
- O DIN boxes with dimensions 48, 72, 96 and 144 mm.
- o Precision class 1,5
- Measurement in D.C. of 0 ... 10 V, 0/4 ... 20 mA, .../60 mV
- o Exchangeable scales for BC48, BC72, BC96, BM 45

Application

For the measurement of the mean value of voltages and currents in direct current circuits, even of the pulsating type, in a vast margin of values.



Page 2 of 2





ZC48 0...10V

Process indicator

Code: M12513.

Specifications

Mechanical characteristics

Size (mm) width x height x depth	48 x 48 x 66.2 (mm)
Fastening	Panel
Weight (kg)	0,075

ZC Process indicators, 240°

CODE	TYPE	Scale	Accuracy	Modules	Full scale
M12523.	ZC72 010V	240° P1	1,5	72x72	010 V
M12521.	ZC72 420mA	240° P1	1,5	72x72	420 mA
M12520.	ZC72/60mV	240° P1	1,5	72x72	/60 mV
M12533.	ZC96 010V	240° P1	1,5	96x96	010 V
M12531.	ZC96 420mA	240° P1	1,5	96x96	420 mA
M12530.	ZC96/60mV	240° P1	1,5	96x96	60 mV

Scales included in the price (*) The 6-digit code includes the 4 \dots 20 mA scale

