



MMC45 .../5A

MMC45 .../5A, Maximeter

Code: M12651. DESCATALOGADO

> Scale: 90°, P1, 2 > Accuracy: 3

> Measurement Range (A): .../5 A

Description

- O Does not need an auxiliary power supply
- o DIN boxes with dimensions 48, 72, 96 and 144
- Measurement in AC of .../5 A (on demand.../ 1 A)
- o Exchangeable scales for MC48, MC72, MC96, MM 45, EMC72, EMC96
- Thermal inertia times of 15 min (on demand, 8 and 30 min)

Application

To control the alternating current and measure long overloads in the same unit, integrated within a determined period.







MMC45 .../5A

Ammeters Maximeters

Code: M12651.

Specifications

Mechanical characteristics	
Size (mm) width x height x depth	85 x 52 x 65 (mm)
Fastening	DIN rail
Weight (kg)	0,14
Environmental characteristics	
Protection class	DIN rail: IP 52 (front), IP 00 (terminals)
Storage temperature	-25+40 °C
Working temperature	+10 +30 °C
Standards	
Certifications	UL
Electrical safety, Maximum height (m)	2000
Standards	BS 89, UNE-EN 60051, IEC 144, UL94, DIN 43780, IEC 51, UNE 21318
Current measurement circuit	
Consumption	3,25 VA
Allowable overload	1,5 In permanent / 15 In during 1s
Electrical characteristics	
Insulation voltage, circuit	2 KV A 50 HZ < 1min entre mecanismo y caja
Measurement accuracy	
Accuracy	± 3 % FE



Scale NOT included