



HC72 45-55Hz 230V

HC72 45-55Hz 230V, Frequencymeter

Code: M12721.

> Scale: 90°

> Accuracy: 0,5

> Measure: 45...55 Hz

> Frequency (Hz): 45...55

> Modules: 72x72

Description

- O Does not need an auxiliary power supply
- O DIN box with dimensions: 48, 72, 96 and 144
- o Class 0.5
- o Built-in electronic converter

Application

Accurate and easy reading of frequency in alternating current circuits. The distortion of voltage (we shall measure its frequency) can reach 15% of the nominal voltage in the third order harmonic, while the Class is not affected.







HC72 45-55Hz 230V

Frequencymeters

Code: M12721.

Specifications

Mechanical characteristics					
Size (mm) width x height x depth	72 x 72 x 49.2 (mm)				
Fastening	Panel				
Weight (kg)	0,147				
Environmental characteristics					
Protection class	Panel: IP 52 (Front), IP 00 (Terminals)				
Storage temperature	-25+40 °C				
Working temperature	+10 +30 °C				
Standards					
Certifications	UL				
Electrical safety, Maximum height (m)	2000				
Standards	BS 89, UNE-EN 60051, IEC 144, UL94, DIN 43780, IEC 51, UNE 21318				
Current measurement circuit					
Allowable overload	1,5 In permanent / 15 In during 1s				
Voltage measurement circuit					
Consumption	2 3 VA				
Sampling frequency	50 400 Hz				
Nominal voltage	230 V ~				
Electrical characteristics					
Insulation voltage, circuit	2kV a 50 Hz < 1min entre mecanismo y caja				
Measurement accuracy					
Accuracy	0,5 % FE				

Pointer type frequencymeters, 90°

Hz 230V 90°	0.5	70	70 /5		
Hz 230V 90°	Λ.5	72	70 /-		
	0,5	/2X	(72 45	i55 Hz	4555
Hz 230V 90°	0,5	96x	x96 45	55 Hz	4555
	Hz 230V 90°	Hz 230V 90° 0,5	Hz 230V 90° 0,5 96:	Hz 230V 90° 0,5 96x96 45	Hz 230V 90° 0,5 96x96 4555 Hz





Page 3 of 4





HC72 45-55Hz 230V

Frequencymeters

Code: M12721.

CODE	TYPE	Scale	Accuracy	Modules	Measure	Frequency (Hz)
M12741.	HC144 45-55Hz 230V	90°	0,5	144x144	4555 Hz	4555









HC72 45-55Hz 230V

Frequencymeters

Code: M12721.

Dimensions





Page 4 of 4