



### **HZC 96**

HZC 96, Frequencymeter

Code: M12831. (CONSULTAR DISPONIBILIDAD)

> Scale: 240°

> Accuracy: 0,5

> Measure: 45...55 Hz

> Frequency (Hz): 45...55

> Modules: 96x96

#### Description

- O Does not need an auxiliary power supply
- O DIN box with dimensions: 48, 72, 96 and 144
- o Class 0.5
- o Built-in electronic converter

#### **Application**

Accurate and easy reading of frequency in alternating current circuits. The distortion of voltage (we shall measure its frequency) can reach 15% of the nominal voltage in the third order harmonic, while the Class is not affected.







## **HZC 96**

Frequencymeters

Code: M12831.

### **Specifications**

Size (mm) width y beight y death	96 x 96 x 101.2 (mm)
Size (mm) width x height x depth	
Fastening	Panel
Weight (kg)	0,18
Environmental characteristics	
Protection class	Panel: IP 52 (Front), IP 00 (Terminals)
Storage temperature	-25+40 °C
Working temperature	+10 +30 °C
Standards	
Certifications	UL
Electrical safety, Maximum height (m)	2000
Standards	BS 89, UNE-EN 60051, IEC 144, UL94, DIN 43780, IEC 51, UNE 21318
Current measurement circuit	
Allowable overload	1,5 In permanent / 15 In during 1s
Voltage measurement circuit	
Consumption	2 3 VA
Sampling frequency	50 400 Hz
Nominal voltage	230 V ~
Electrical characteristics	
Insulation voltage, circuit	2kV a 50 Hz < 1min entre mecanismo y caja
Measurement accuracy	
Accuracy	0,5 % FE









## **HZC 96**

Frequencymeters

Code: M12831.

# **Dimensions**





Page 3 of 3