



2HLC96 47-53Hz

2HLC96 47-53Hz

Code: M12932. (DESCATALOGADO)

- > Frequencymeter
- > Accuracy: 0,5
- > Measure: 47...53 Hz
- > Scale: -
- > Frequency (Hz): 47...53
- > 13 láminas

Specifications

Environmental characteristics

Protection class	Panel: IP 52 (Front), IP 00 (Terminals)
Storage temperature	-25...+40 °C
Working temperature	+10 ... +30 °C

Standards

Certifications	UL
Electrical safety, Maximum height (m)	2000
Standards	BS 89, UNE-EN 60051, IEC 144, UL94, DIN 43780, IEC 51, UNE 21318

Voltage measurement circuit

Consumption	1 ... 3,6 VA
Sampling frequency	47 ... 53 Hz
Nominal voltage	230 V ~
Maximum permanent measurement voltage	1,2 Vn permanent rated voltage / 2 Vn during 5s

Electrical characteristics

Insulation voltage, circuit	2kV a 50 Hz < 1min entre mecanismo y caja
-----------------------------	---

Mechanical characteristics

Weight (kg)	0,4
-------------	-----

Measurement accuracy

Accuracy	0,5 % FE
----------	----------



2HLC96 47-53Hz

Frecuencymeter, marine applications equipment

Code: M12932.