

FMZ144 110V

FMZ144 110V, Phasemeter

- Code: M13544. DESCATALOGADO
- > Scale: 240° P1
- > System: Single-phase
- > Accuracy: 1,5
- > Measurement Range (V): 110
- > Modules: 144x144

Description

- Does not need an auxiliary power supply
- $\circ~$ DIN box with dimensions 96 and 144 mm.
- \circ Precision class 1,5
- Built-in electronic converter
- Balanced single and three-phase circuits

Application

Measurement of $\cos \phi$ in balanced or unbalanced single and three-phase circuits

Circutor



FMZ144 110V

Phasemeters

Code: M13544.

Specifications

Size (mm) width x height x depth	144 x 144 x 71.8 (mm)
Fastening	Panel
Weight (kg)	0,71
invironmental characteristics	
Protection class	Panel: IP 52 (Front), IP 00 (Terminals)
Storage temperature	-25+40 °C
Working temperature	+10 +30 °C
Standards	
Certifications	UL
Electrical safety, Maximum height (m)	2000
Standards	BS 89, UNE-EN 60051, IEC 144, UL94, DIN 43780, IEC 51, UNE 21318
Current measurement circuit	0,75 VA
Sampling frequency	20 100 Hz
Nominal current (In)	5 A
Allowable overload	1,2 In permanent / 5 In during 30s / 10 In during 5s / 40 In during 1s
/oltage measurement circuit	
Consumption	4 VA
Sampling frequency	40 70 Hz
Maximum permanent measurement voltage	1,2 Vn permanent rated voltage / 2 Vn during 5s
Electrical characteristics	
Insulation voltage, circuit	2 kV, 50 Hz, 1 min entre mecanismo y caja
Measurement accuracy	
Accuracy	± 1,5 % FE

Current range: 0.1 to 1.2 In. For the connection of transformers .../5A. Built-in electronic transducer.





FMZ144 110V

Phasemeters

Code: M13544.

Dimensions

Connections

×

×

