



## PIC96A 400 V

PIC96A 400 V, Phasemeter

Code: M13633. DESCATALOGADO

- > Scale: 360°, P1
- > System: Single-phase
- > Accuracy: 1,5
- > Measurement Range (V): 400
- > Modules: 96x96

### Description

- Does not need an auxiliary power supply
- DIN box with dimensions 96 and 144.
- Class 1.5
- Balanced and unbalanced single and three-phase circuits.
- 4 quadrants

### Application

Measurement of  $\cos \phi$  in balanced or unbalanced single and three-phase circuits.



# PIC96A 400 V

Phasemeters

Code: M13633.

## Specifications

### Mechanical characteristics

|                                  |                      |
|----------------------------------|----------------------|
| Size (mm) width x height x depth | 96 x 96 x 101.2 (mm) |
| Fastening                        | Panel                |
| Weight (kg)                      | 1,91                 |

### Environmental characteristics

|                     |   |
|---------------------|---|
| Protection class    | Panel: IP 52 (Front), IP 00 (Terminals) |
| Storage temperature | -25...+40 °C                            |
| Working temperature | +10 ... +30 °C                          |

### Standards

|                                       |   |
|---------------------------------------|---|
| Certifications                        | CE, UL  |
| Electrical safety, Maximum height (m) | 2000  |
| Standards                             | BS 89, UNE-EN 60051, IEC 144, UL 94, DIN 43780, IEC 51, UNE 21318 |

### Current measurement circuit

|                      |  |
|----------------------|--|
| Consumption          | 4 VA   |
| Sampling frequency   | 20 ... 100 Hz  |
| Nominal current (In) | ... 5 A  |
| Allowable overload   | 1,2 In permanent / 5 In during 30s / 10 In during 5s / 40 In during 1s |

### Voltage measurement circuit

|                    |                                     |
|--------------------|-------------------------------------|
| Consumption        | 5 VA                                |
| Sampling frequency | 49,5 ... 50,5 Hz / 59,4 ... 60,6 Hz |

### Electrical characteristics

|                             |  |
|-----------------------------|--|
| Insulation voltage, circuit | 2 kV a 50 Hz <1 min entre mecanismo y caja |
|-----------------------------|--|

### Measurement accuracy

|          |            |
|----------|------------|
| Accuracy | ± 1,5 % FE |
|----------|------------|

Current range: 0.1 to 1.2 In. For the connection of transformers .../5A.



## PIC96A 400 V

Phasemeters

Code: M13633.

## Dimensions



## Connections

