



UC72 150...500V

UC72 150...500V, Sequence-Ind.

Code: M13721. CONSULTAR DISPONIBILIDAD

> Measurement Range (V): 150...500

> Device: UC72 > Modules: 72x72

Description

A completely electronic circuit without moving parts allows easily activation of LED

Application

UC72 and UC96 types indicate the phase sequence type in three-phase networks. CUC96, besides indicating the phase sequence type, have a realy with a free voltage switch-over contact. The relay opens in voltage lack situation or when the phase rotation sense is wrong.







UC72 150...500V

Code: M13721.

Specifications

Mechanical characteristics	
Size (mm) width x height x depth	72 x 72 x 62.9 (mm)
Fastening	Panel
Weight (kg)	0,145
Environmental characteristics	
Protection class	Panel: IP 52 (Front), IP 00 (Terminals)
Storage temperature	-40 +70 °C
Working temperature	0 +70 °C
Standards	
Certifications	CE
Electrical safety, Maximum height (m)	2000
Standards	BS 89, UNE-EN 60051, IEC 144, DIN 43780, IEC 51, UNE 21318
Current measurement circuit	
Consumption	3 mA
Sampling frequency	50 Hz
Voltage measurement circuit	
Nominal voltage	230 V~ (optional 100-120 V~ / 380-440 V~)
Maximum permanent measurement voltage	1,2 Vn permanent rated voltage / 2 Vn during 5s
Measurement accuracy	
Accuracy	1,5 % FE







UC72 150...500V

Code: M13721.

Dimensions Connections



