



CUC96 400V

CUC96 400V, Sequence-Ind.

Code: M13755. DESCATALOGADO

> N° relays: 1

> Measurement Range (V): 400

> Device: CUC96 > Modules: 96x96

Description

A completely electronic circuit without moving parts allows easily activation of LED

Application

UC72 and **UC96** types indicate the phase sequence type in three-phase networks. **CUC96**, besides indicating the phase sequence type, have a realy with a free voltage switch-over contact. The relay opens in voltage lack situation or when the phase rotation sense is wrong.







CUC96 400V

Phase sequence indicators

Code: M13755.

Specifications

Mechanical characteristics	
Size (mm) width x height x depth	96 x 96 x 62.9 (mm)
Fastening	Panel
Weight (kg)	0,375
Environmental characteristics	
Protection class	Panel: IP 52 (Front), IP 00 (Terminals)
Storage temperature	-40 +70 °C
Working temperature	0 +70 °C
Standards	
Certifications	CE
Electrical safety, Maximum height (m)	2000
Standards	BS 89, UNE-EN 60051, IEC 144, DIN 43780, IEC 51, UNE 21318
Current measurement circuit	
Consumption	4 VA
Sampling frequency	50 Hz
Voltage measurement circuit	
Nominal voltage	230 V~ (optional 100-120 V~ / 380-440 V~)
Maximum permanent measurement voltage	1,2 Vn permanent rated voltage / 2 Vn during 5s
Measurement accuracy	
Accuracy	1,5 % FE







CUC96 400V

Code: M13755.

Dimensions Connections



