





STC96 110V

STC96 110V, Synchronoscope

Code: M14435. CONSULTAR DISPONIBILIDAD

> System: Three-phase

> Accuracy: 1,5

> Measurement Range (V): 110

> Device: STC96 > Modules: 96x96

Description

- O Does not need an auxiliary power supply
- o DIN box with dimensions: 96 and 144 mm
- o Class 1
- o For single and three-phase circuits
- o Does not need an auxiliary power supply
- O DIN box with dimensions: 72 and 96 mm
- o Class 1.5
- o Built-in voltage relay
- Low consumption

Application

To provide a correct reading of the difference between the frequency and phase angle between two generators or a generator and the network, when connected in parallel. When the difference is zero, the instrument's needle does not move from the synchronization mark located in the centre of the scale.

The instrument scale is divided in two areas marked with the (+) and (-) signs. These signs indicate whether the machine being connected has a higher or lower frequency that the other one, respectively. Synchronism is achieved when the needle is on the (-) side, slowly turning towards (+). The needle of the instrument starts to turn in the correct direction when the difference in frequencies is 1.5 Hz for three-phase systems or 0.5 Hz for single-phase systems.







STC96 110V

Synchronization and marine applications equipment

Code: M14435.

Specifications

Electrical characteristics	
Frequency	50/60 Hz.
Permanent overload	1,2 Un
Mechanical characteristics	
Size (mm) width x height x depth	96 x 96 x 101.2 (mm)
Fastening	Panel
Weight (kg)	0,74
Environmental characteristics	
Operating temperature	+10 +30 °C
Standards	
Electrical safety, Maximum height (m)	2000









STC96 110V

Synchronization and marine applications equipment

Code: M14435.

Connections



