



## CEC96 250V

CEC96 250V, Voltmeter

Code: M14822. DESCATALOGADO

- > Scale: 90°, P1
- > Accuracy: 1,5
- > Measurement Range (V): 250
- > Modules: 96x96

### Description

Voltmeter:

- Does not need an auxiliary power supply, only CEC 96.
- DIN box with dimensions 48, 72, 96 and 144 mm.
- Precision class 1,5
- Measurement in true root mean square or U ... 600 V a.c.
- Exchangeable scales for EC 48, EC 72, EC 96, EM 45
- The alarm system can be fully configured for CBC 96

### Application

In direct current applications, to control the state of the current quickly and visually.



# CEC96 250V

Voltmeters with 2 relays

Code: M14822.

## Specifications

AC power supply	
Consumption	2,5 VA
Frequency	40...90 HZ
Nominal voltage	230 Vca
Mechanical characteristics	
Size (mm) width x height x depth	96 x 96 x 85.3 (mm)
Weight (kg)	0,435
Environmental characteristics	
Protection class	Panel: IP 52 (Front), IP 20 (Terminals)
Storage temperature	-25...+70 °C
Working temperature	+5 ... + 55 °C
Voltage measurement circuit	
Consumption	0,2 VA
Sampling frequency	45...65 Hz
Maximum permanent measurement voltage	1,2 Vn permanent rated voltage / 2 Vn during 5s
Electrical characteristics	
Insulation voltage, circuit	3 kV, 50 Hz, 1 min
Standards	
Electrical safety, Maximum height (m)	2000
Standards	IEC 51, IEC 1010, IEC 529, IEC 255, IEC 278, IEC 414, IEC 144, LLOYD'S (TEST. ESP. N° 1)
Measurement accuracy	
Accuracy	1,5 % FE

CEC-V  
Moving Iron Voltmeters (ac), 2 relays

CODE	TYPE	Scale	Accuracy	Modules
M14821.	CEC96 150V	90° , P1	1,5	96x96
M14824.	CEC96 400V	90° , P1	1,5	96x96



## CEC96 250V

Voltmeters with 2 relays

Code: M14822.

## Dimensions

