



## CEC96 300V

CEC96 300V, Voltmeter

Code: M14823. DESCATALOGADO

- > Scale: 90°, P1
- > Accuracy: 1,5
- > Measurement Range (V): 300
- > Modules: 96x96

### Description

Voltmeter:

- Does not need an auxiliary power supply, only CEC 96.
- DIN box with dimensions 48, 72, 96 and 144 mm.
- Precision class 1,5
- Measurement in true root mean square or U ... 600 V a.c.
- Exchangeable scales for EC 48, EC 72, EC 96, EM 45
- The alarm system can be fully configured for CBC 96

### Application

In direct current applications, to control the state of the current quickly and visually.



## CEC96 300V

Voltmeters with 2 relays

Code: M14823.

### Specifications

#### AC power supply

Consumption	2,5 VA
Frequency	40...90 Hz
Nominal voltage	230 Vca

#### Mechanical characteristics

Size (mm) width x height x depth	96 x 96 x 85.3 (mm)
Weight (kg)	0,435

#### Environmental characteristics

Protection class	Panel: IP 52 (Front), IP 20 (Terminals)
Storage temperature	-25...+70 °C
Working temperature	+5 ... +55 °C

#### Voltage measurement circuit

Consumption	0,2 VA
Sampling frequency	45...65 Hz
Maximum permanent measurement voltage	1,2 Vn permanent rated voltage / 2 Vn during 5s

#### Electrical characteristics

Insulation voltage, circuit	3 kV, 50 Hz, 1 min
-----------------------------	--------------------

#### Standards

Electrical safety, Maximum height (m)	2000
Standards	IEC 51, IEC 1010, IEC 529, IEC 255, IEC 278, IEC 414, IEC 144, LLOYD'S (TEST. ESP. N° 1)

#### Measurement accuracy

Accuracy	1,5 % FE
----------	----------

#### CEC-V

Moving Iron Voltmeters (ac), 2 relays

CODE	TYPE	Scale	Accuracy	Modules
M14821.	CEC96 150V	90°, P1	1,5	96x96



## CEC96 300V

Voltmeters with 2 relays

Code: M14823.

### Dimensions

