



## CH48

CH48, Hour run meter

Code: M14911.

- > Frequency (Hz): 50
- > Display: Visualizador electromecánico
- > Modules: 48x48

### Application

- Timers are used to measure time with a simple, easy and reliable system.
- Measurement of start-up and operating times.
- Modification and operating times.
- Production and quantity times.
- Data to provide information about the following



# CH48

Hour run meters

Code: M14911.

## Specifications

### AC power supply

Frequency	50/60 Hz
Nominal voltage	230 Vca

### Mechanical characteristics

Size (mm) width x height x depth	48 x 48 x 48 (mm)
Fastening	Panel
Weight (kg)	0,042

### Environmental characteristics

Protection class	Panel: IP 52 (Front), IP 00 (Terminals)
Storage temperature	-25...+40 °C
Working temperature	+10 ... +30 °C

### Standards

Certifications	CE
Standards	BS 89, UNE-EN 60051, IEC 144, DIN 43780, IEC 51, UNE 21318

### Current measurement circuit

Consumption	10 mA
-------------	-------

### User interface

Display format	1,5 x 3,5 mm mit lupe
Range	99999,99
Display type	Mechanic

CH  
Hour run meters

CODE	TYPE	Modules	Frequency (Hz)
M14911.	CH48	48x48	50
M14921.	CH72	72x72	50
M14931.	CH96	96x96	50
M14951.	CH45		50




## CH48

Hour run meters

Code: M14911.

### Dimensions



### Connections

