





## **CH45**

CH45, Hour run meter

Code: M14951.

- > Frequency (Hz): 50
- > Display: Visualizador electromecánico

### **Application**

- $\circ\;$  Timers are used to measure time with a simple, easy and reliable system.
- Measurement of start-up and operating times.
- $\circ\;$  Modification and operating times.
- o Production and quantity times.
- $\circ\;$  Data to provide information about the following







# **CH45**

Hour run meters

Code: M14951.

### **Specifications**

AC power supply		
Frequency	50/60 Hz	
Nominal voltage	230 Vca	
Mechanical characteristics		
Size (mm) width x height x depth	90 x 36 x 55 (mm)	
Fastening	DIN rail	
Weight (kg)	0,07	
Environmental characteristics		
Protection class	Panel: IP 52 (Front), IP 00 (Terminals)	
Storage temperature	-25+40 °C	
Working temperature	+10 +30 °C	
Standards		
Certifications	CE	
Standards	BS 89, UNE-EN 60051, IEC 144, DIN 43780, IEC 51, UNE 21318	
Current measurement circuit		
Consumption	10 mA	
User interface		
Display format	1,5 x 3,5 mm mit lupe	
Range	99999,99	
Display type	Mechanic	

#### $\mathsf{CH}$

Hour run meters

CODE	TYPE	Modules	Frequency (Hz)
M14911.	CH48	48x48	50
M14921.	CH72	72x72	50
M14931.	CH96	96x96	50
M14951.	CH45		50







# **CH45**

Hour run meters

Code: M14951.

#### Dimensions



### Connections



