



MC96 .../5A 120%

MC96 .../5A 120%, Maximetro

Code: M15531.

- > Scale: 90°, P1, 2
- > Accuracy: 3
- > Measurement Range (A): .../5 A
- > Modules: 96x96

Specifications

Mechanical characteristics

| | |
|----------------------------------|---------------------|
| Size (mm) width x height x depth | 96 x 96 x 49.2 (mm) |
| Weight (kg) | 0,14 |

Environmental characteristics

| | |
|---------------------|---|
| Protection class | Panel: IP 52 (Front), IP 00 (Terminals) |
| Storage temperature | -25 ... +40 °C |
| Working temperature | +10 ... +30 °C |

Standards

| | |
|---------------------------------------|--|
| Certifications | UL |
| Electrical safety, Maximum height (m) | 2000 |
| Standards | BS 89, EN 60051, IEC 144, UL94, DIN 43780, IEC 51, UNE 21318 |

Current measurement circuit

| | |
|--------------------|------------------------------------|
| Consumption | 3,25 VA |
| Allowable overload | 1,5 In permanent / 15 In during 1s |

Electrical characteristics

| | |
|-----------------------------|--|
| Insulation voltage, circuit | 2 KV A 50 HZ < 1min entre mecanismo y caja |
|-----------------------------|--|

Measurement accuracy

| | |
|----------|----------|
| Accuracy | ± 3 % FE |
|----------|----------|

MC

Maximeter ammeters

| CODE | TYPE | Scale | Accuracy | Measurement Range (A) | Modules |
|---------|------------------|------------|----------|-----------------------|---------|
| M12211. | MC48 .../5 A | 90°, P1, 2 | 3 | .../5 A | 48x48 |
| M12221. | MC72 .../5A | 90°, P1, 2 | 3 | .../5 A | 72x72 |
| M15521. | MC72 .../5A 120% | 90°, P1, 2 | 3 | .../5 A | 72x72 |
| M12231. | MC96 .../5 A | 90°, P1, 2 | 3 | .../5 A | 96x96 |
| M15531. | MC96 .../5A 120% | 90°, P1, 2 | 3 | .../5 A | 96x96 |
| M12241. | MC144 .../5A | 90°, P1, 2 | 3 | .../5 A | 144x144 |



MC96 .../5A 120%

Code: M15531.

Scale NOT included



MC96 .../5A 120%

Code: M15531.

Connections

