



DM45-A

DM45-A, Ammeter

Code: M20911. DESCATALOGADO

> N° relays: 1 > System: AC

> Measure: ... / 5 Aac> Paramètre: Ammeter> Mounting: DIN rail

Description

- o Electrical parameter indicator equipment
- o Its design enables the installation of the unit on small panels
- $\circ~$ It measures voltage, current, frequency and harmonic distortion, depending on the type
- o Fully sealed
- o Fully programmable alarm relay
- Robust and compact
- O Stores maximum and minimum values

Application

- O Displays one or various electrical parameters of a sub-panel, control process or determined machine.
- Alarm system: the unit's internal relay can act on contactors, sound and/or light devices to carry out a protection or warning operation.









DM45-A

Digital instruments, DIN rail

Code: M20911.

Specifications

| Consumption | 5 VA | |
|--|---|--|
| Frequency | 4070 Hz. | |
| Nominal voltage | 115 / 230 Vc.a | |
| | | |
| Mechanical characteristics | | |
| Size (mm) width x height x depth | 36 x 85 x 63.8 (mm) | |
| Envelope | Self-extinguishing ABS | |
| Weight (kg) | 0,193 | |
| Environmental characteristics | | |
| Protection class | IP 20 / IP 54 with terminal cover (optional) (for models Ø 85, 100, 116 mm) | |
| Relative humidity (without condensation) | 595 % | |
| Storage temperature | -40+70 °C | |
| Working temperature | -20+50 °C | |
| Current measurement circuit | | |
| Allowable overload | 1,2 In permanent | |
| Refresh rate | 1 lectura/s | |
| Maximum current | 5 Ac.a. | |
| Minimum current measurement | 0,05 Aac | |
| Resolution | 10 bits | |
| Voltage measurement circuit | | |
| Consumption | 0,6 VA | |
| User interface | | |
| LED | 4 | |
| Range | 0,0009999 | |
| Resolution of the display | 30 | |
| Display type | 7 segments (4 digits), red | |
| Standards | | |
| Standards | EN 61000-6-3, EN 61000-6-1, IEC 61010-1, IEC 60664 | |
| Digital relay outputs | | |
| Contact-coil insulation | 2000 Vc.a. | |
| Contact-contact insulation | 750 Vc.a. | |
| Nominal current | 5 Aac | |









DM45-A

Digital instruments, DIN rail

Code: M20911.

| Maximum open contact voltage | 250 Vac | |
|------------------------------|-----------|--|
| Resistive load (max.) | 750 VA | |
| Insulation resistance | > 1000 MΩ | |

Other information of interest: Size: 2 modules







Circutor

DM45-A

Digital instruments, DIN rail

Code: M20911.

Dimensions

Connections





