



DHB-124, Digital indicator

Code: M22022. DESCATALOGADO

> Communications: RS-485

> N° relays: 3

> Analog output: 1 (0/4...20 mA) |1(0...10V)

> Measure: imp., Hz.

> Paramètre: Impulses, frequency, circular speed, periods, worktime, encoder position

> Mounting: Pannel

#### Description

Panel mounted digital devices designed to display on-screen the value of a electrical variable measured or proportional value of a process signal, depending on the model. Essential for regulation purposes, programming the analogue output available in some models, and for control purposes, if the relay outputs are used as alarms.

DHB units are fully programmable and the following can be programmed: scale, transformation ratios, alarm setpoints to activate relays, communications, colour of the numbers displayed on screen, etc. Depending on the model, you can measure the electrical parameters of a single-phase installation such as voltage, current, frequency, power,  $\cos \varphi$ , etc., the direct voltage or current of an installation, impulses, frequency, circular speed, periods, time, temperature and also other voltage and current process variables. AC models calculate the true root mean square measure (TRMS).

The models include the following common features:

- o IP 65 front panel
- High measurement accuracy
- o Programmable measurement input
- O Delay and latching alarms
- o 24 Vdc output for supply external transducers (DHB 1xx and DHB 4xx models)
- o Galvanic insulation between external circuits
- Adjustment of non-linear equations with 21 straight points (2 in the DHB 3xx model).
- O Change in colour of the display depending on the value shown.
- Maximum and minimum values
- o Clock with current time
- o Self-configurable decimal point
- Compatible with Power Studio (model with communications)
- o Installation on 96 x 48 mm panel

#### **Application**

These digital instruments have multiple applications. Thanks to their very bright 5-digit and 3-colour screen, you can simply view a numerical value and an alarm or prealarm status of a measured variable. Depending on the model selected, displayed on-screen are the electrical parameters of a single-phase installation as a power analyzer (voltage, current, power, frequency, etc.).

Other models allow to visualize the value of an analogue signal, show impulses received through an input, temperature, time, circular speed and many other variables that depends on the device and the configuration. The indicators also let you operate any external element, using the panel unit outputs as alarms depending on the value of a variable or as a transducer of the measured variable to an analogue signal, which is subsequently sent to another unit, such as a PLC.

Apart from displaying the values, units with communications also allow you to send data via the RS-485 communication bus for software or PLC integration.







Panel mounted digital instruments

Code: M22022.

### **Specifications**

AC power supply	
Installation category	CAT III 300V
Consumption	1,29 VA
Frequency	40400 Hz
Nominal voltage	85253 Vc.a.
DC power supply	
Installation category	CAT III 300 V
Consumption	1,26 W
Nominal voltage	85253 Vdc
Mechanical characteristics	
Size (mm) width x height x depth	96 x 48 x 93 (mm)
Envelope	Self-extinguishing V0 plastic
Weight (kg)	0,3
Environmental characteristics	
Protection class	IP 65 (Front), IP 10 (rear)
Relative humidity (without condensation)	2595 %
Storage temperature	-33+70 °C
Working temperature	-25+55 °C
Standards	
Electrical safety, Maximum height (m)	2000
Standards	UNE EN 61000-6-2, UNE EN 61000-6-4, UNE EN 61010-1
User interface	
LED	7
Keyboard	4 keys
Display type	7 segments (5 digits) LED
Analogue outputs	
Current mode, nominal range	020 mA or 420 mA
Current mode: minimum load resistance	≤ 500Ω
Voltage mode, minimum load resistance	≥ 500Ω
Voltage mode: nominal output range	010 Vdc
Digital relay outputs	
Maximum current	0,5 A







Panel mounted digital instruments

Code: M22022.

1x10 <sup>5</sup> ciclos (250 Vc.a./5 A)
1x10 <sup>6</sup> cycles
1500 W o 1250 VA
0,01
0 99999 h
-19999 99999
<10 kHz : 0,0599999 Hz / >10 kHz : 199999 Hz
00:00 23:59
-1999999999
<10 s (0,0001 11s) / >10 s (0,0001 3600s)
0,0599999 rpm
NPN
30 Vc.c. / 30 mA
24 Vc.c. / 30 mA
5 36 Vc.c.
10 kHz
<10 kHz : 100 kHz / >10kHz: 1MHz
CTO KITZ . TOO KITZ 7 7 TOKITZ. IT TITE
100 kHz







Panel mounted digital instruments

Code: M22022.

Dimensions Connections





