



DCB-72 Vac-20R, digital voltmeter, 72 x 72, 2 output relays

Code: M22212.

> Scale: 63,5 V / 100 V / 110 V /230 V /380 V /480 V

> N° relays: 2 > System: AC > Mounting: Pannel > Modules: 72 x 72

Description

Panel-mounted digital instruments that display the value of an electrical variable measured or proportional value of a process signal on its screen (depending on the model). Designed to supervise, regulate and control units with the use of relay outputs that are built in the unit.

The DCB series displays the value of an electrical variable measured or proportional value of a process signal on its screen (depending on the model). The unit displays the electrical parameters of a single-phase installation, depending on the model, such as the voltage, current, etc. In DC systems, the unit can measure the voltage, current, frequency and other variables associated with industrial processes. The AC models take the measurements in true RMS (TRMS).

All models in this range have the following features:

- \circ Universal power supply at 80 ... 270 $V_{ac/dc}$ and optional power supply at 24 V_{dc}
- o IP 54 protection degree on the front panel
- High measurement accuracy
- O Programmable measuring input
- Alarm delays and interlockings
- o Galvanic insulation between external circuits
- o Self-configurable decimal point
- O Can be installed on 48 x 48 or 72 x 72 mm panels, depending on the model

Application

These digital instruments have many different applications and can be used in:

- Industrial applications
- Air conditioning units
- o Solar photovoltaic energy installations
- o Industrial process control systems







Panel-mounted digital instruments

Code: M22212.

Specifications

AC power supply	
Installation category	CAT III 300 V
Consumption	1.7 4 VA
Frequency	50/60 Hz
Nominal voltage	80270 V ~
DC power supply	
Installation category	CAT III 300 V
Nominal voltage	80270 Vdc
Environmental characteristics	
Protection class	Front: IP54, Rear: IP20
Relative humidity (without condensation)	≤ 95 %
Storage temperature	-40 +85 °C
Working temperature	-40 +70 °c
Mechanical characteristics	
Envelope	Polycarbonate + ABS
Weight (kg)	0,216
Voltage measurement circuit	
Installation category	CAT III 300 V
Consumption	< 0.2 VA
Sampling frequency	4565 Hz
Input impedance	> 1.7 MΩ
Frequency measuring range	4565 Hz
Nominal voltage	63.5 V \sim / 100 V \sim / 110 V \sim / 230 V \sim / 380 V \sim / 480 V \sim
Maximum permanent measurement voltage	1.2 Un continous, 2 Un instantaneous (1 min)
Standards	
Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300 V
Electrical safety, Contamination level/class	Pollution resistance 2
Standards	IEC 61010-1, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11
User interface	
Keyboard	4 keys
Display type	LED 5 digits







Panel-mounted digital instruments

Code: M22212.

Digital relay outputs

Quantity	2	
Maximum current	5 A ~	
Maximum open contact voltage	277 V ~	
Electrical life	(250 V ~ / 5 A) 1 x 10 ⁵	
Mechanical life	5 x 10 ⁶	
Maximum switching capacity	1250 VA	

Measurement accuracy

Phase voltage measurement	0.5 %	

DCB

Digital instrument

CODE	TYPE	Scale	N° relays	System	Modules
Voltmeters					
M22212.	DCB-72 Vac-20R	63,5 V / 100 V / 110 V /230 V /380 V /480 V	2	AC	72 x 72







Panel-mounted digital instruments

Code: M22212.

Dimensions Connections



