



## DHC-96 Adc

DHC-96 Adc, digital ammeter, 96 x 48, 2 output relays

Code: M22378.

- > Protocol: Modbus/RTU
- > Scale: 1 Adc / 5 Adc
- > IP: 54
- > Communications: RS-485
- > N° relays: 2
- > Digital inputs: 2
- > Analog output: 1 (20 mA)
- > System: DC
- > Parameter: A dc
- > Mounting: Pannel
- > Modules: 96 x 48

### Description

Panel-mounted digital instruments that display the value of an electrical variable measured or proportional value of a process signal on its screen (depending on the model). Designed to supervise, regulate and control units with the use of relay outputs that are built in the unit.

The **DHC-96** series displays the value of an electrical variable measured or proportional value of a process signal on its screen (depending on the model). The unit displays the electrical parameters of a single-phase installation, depending on the model, such as the voltage, current, etc. In DC systems, the unit can measure the voltage, current, frequency and other variables associated with industrial processes. The AC models take the measurements in true RMS (TRMS).

All models in this range have the following features:

- Universal power supply at 80...270 V<sub>ac/dc</sub> (DHC-96-CPM: 100...270 Vac/dc) and optional power supply at 16 ... 36 V<sub>dc</sub> (DHC-96-CPM: 20...60 Vdc)
- IP 54 protection degree on the front panel
- High measurement accuracy
- Programmable measuring input
- Alarm delays and interlockings
- Galvanic insulation between external circuits
- Self-configurable decimal point
- Installed on 96 x 49 mm panels

### Application

These digital instruments have many different applications and can be used in:

- Industrial applications
- Air conditioning units
- Solar photovoltaic energy installations
- Industrial process control systems



## DHC-96 Adc

Panel-mounted digital instruments

Code: M22378.

### Specifications

#### AC power supply

|                       |              |
|-----------------------|--------------|
| Installation category | CAT III 300V |
| Consumption           | 2.7 ... 5 VA |
| Frequency             | 50/60 Hz     |
| Nominal voltage       | 80...270 V ~ |

#### DC power supply

|                       |               |
|-----------------------|---------------|
| Installation category | CAT III 300 V |
| Consumption           | 1.5 ... 1.6 W |
| Nominal voltage       | 80...270 Vdc  |

#### Mechanical characteristics

|                                  |                     |
|----------------------------------|---------------------|
| Size (mm) width x height x depth | 96 x 49 x 89.2 (mm) |
| Envelope                         | Polycarbonate + ABS |
| Weight (kg)                      | 0,2                 |

#### Environmental characteristics

|  |                           |
|--|---------------------------|
| Protection class                         | Frontal: IP54, Rear: IP20 |
| Relative humidity (without condensation) | ≤ 95 %                    |
| Storage temperature                      | -40 ... +85 °C            |
| Working temperature                      | -40 ... +70 °C            |

#### Current measurement circuit

|                       |  |
|-----------------------|--|
| Installation category | CAT III 300 V                              |
| Consumption           | < 0.2 VA                                   |
| Nominal current (In)  | 1 A / 5 A dc                               |
| Allowable overload    | 1.2 In continuous, 10 In instantaneous(5s) |

#### Standards

|  |   |
|--|---|
| Electrical safety, Maximum height (m)    | 2000  |
| Electrical safety, Installation category | CAT III 300 V   |
| Standards                                | IEC 61010-1, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11 |

#### User interface

|              |              |
|--------------|--------------|
| Keyboard     | 4 keys       |
| Display type | LCD 5 digits |

#### Digital inputs



## DHC-96 Adc

Panel-mounted digital instruments

Code: M22378.

|                               |                        |
|-------------------------------|------------------------|
| Input/output insulation       | 2000 V ~               |
| Quantity                      | 2                      |
| Type                          | Potential-free contact |
| Maximum short-circuit current | 3.3 mA dc              |
| Maximum open circuit voltage  | 17 Vdc                 |

### Analogue outputs

|                                       |                                      |
|---------------------------------------|--------------------------------------|
| Quantity                              | 1                                    |
| Linearity                             | 0.5 %                                |
| Current mode, nominal range           | 0 ... 20 mA, 4 ... 20 mA, 4-12-20 mA |
| Current mode: maximum load resistance | 350 Ω                                |
| Maximum internal voltage              | 17 V dc                              |

### Digital relay outputs

|                              |                                 |
|------------------------------|---------------------------------|
| Quantity                     | 2                               |
| Resistive load (max.)        | 250 Vca / 5 Aca, 30 Vcc / 5 Acc |
| Maximum current              | 5 A ~                           |
| Maximum open contact voltage | 277 V ~                         |
| Electrical life              | 1 x 10 <sup>5</sup>             |
| Maximum switching capacity   | 1385 VA                         |

### Measurement accuracy

|                           |       |
|---------------------------|-------|
| Phase current measurement | 0.5 % |
|---------------------------|-------|

### Serial communication

|                   |            |
|-------------------|------------|
| Protocol          | ModBus RTU |
| Technology / Type | RS-485     |

### DHC-96

Digital instruments 96 x 48

| CODE              | TYPE        | Protocol   | Scale  | Communications | N° relays | Analog output | System | Paramètre | Modules | Measure                        | Power supply (Vac) |
|-------------------|-------------|------------|--|----------------|-----------|---------------|--------|-----------|---------|--------------------------------|--------------------|
| <b>Voltmeters</b> |             |            |  |                |           |               |        |           |         |                                |                    |
| M22318.           | DHC-96 Vac  | Modbus/RTU | 63,5 V / 100 V / 110 V / 230 V / 380 V / 480 V | RS-485         | 2         | 1 (20 mA)     | AC     | V ~       | 96 x 48 |                                |                    |
| M22388.           | DHC-96 Vdc  | Modbus/RTU | ± 10 Vdc / ± 24 Vdc / ± 48 Vdc                 | RS-485         | 2         | 1 (20 mA)     | DC     | Vdc       | 96 x 48 | ± 10 Vdc / ± 24 Vdc / ± 48 Vdc | 80 ... 270 Vac/Vdc |
| M22338.           | DHC-96 HVdc | Modbus/RTU | ± 1500 V                                       | RS-485         | 2         | 1 (20 mA)     | DC     | Vdc       | 96 x 48 |                                |                    |
| <b>Ammeters</b>   |             |            |  |                |           |               |        |           |         |                                |                    |



## DHC-96 Adc

Panel-mounted digital instruments

Code: M22378.

| CODE                      | TYPE         | Protocol   | Scale                                    | Communications | N° relays | Analog output | System | Paramètre | Modules | Measure | Power supply (Vac) |
|---------------------------|--------------|------------|--|----------------|-----------|---------------|--------|-----------|---------|---------|--------------------|
| M22348.                   | DHC-96 mVdc  | Modbus/RTU | 60 mV / 75 mV / 100 mV / 150 mV / 200 mV | RS-485         | 2         | 1 (20 mA)     | DC     | V dc      | 96 x 48 |         |                    |
| M22358.                   | DHC-96 Aac   | Modbus/RTU | 1 A~ / 5 A~                              | RS-485         | 2         | 1 (20 mA)     | AC     | A ~       | 96 x 48 |         |                    |
| M22378.                   | DHC-96 Adc   | Modbus/RTU | 1 Adc / 5 Adc                            | RS-485         | 2         | 1 (20 mA)     | DC     | A dc      | 96 x 48 |         |                    |
| <b>Process indicators</b> |              |            |  |                |           |               |        |           |         |         |                    |
| M22328.                   | DHC-96 LVdc  | Modbus/RTU | ± 10 V                                   | RS-485         | 2         | 1 (20 mA)     | DC     | Vdc       | 96 x 48 |         |                    |
| M22368.                   | DHC-96 mAAdc | Modbus/RTU | -20 ... +20 mA / 0...20 mA / 4...20 mA   | RS-485         | 2         | 1 (20 mA)     | DC     | mAdc      | 96 x 48 |         |                    |

Option of 0/2...10 VDC outputs on demand



## DHC-96 Adc

---

Panel-mounted digital instruments

Code: M22378.

## Dimensions

---



## Connections

---

