

DCP-96 VAC

DCP-96 VAC, Three-phase digital voltmeter

Code: M22410. **DESCATALOGADO**

> Scale: 3 x 230 / 400V
> System: AC
> Paramètre: V, Hz
> Mounting: Pannel
> Modules: 96 x 96

Description

DCP-96 is a new family of panel meters that measure voltage or current (depending on the type) in single-phase and three-phase networks, with or without neutral.
Measurement is performed using true RMS (TRMS), via three AC voltage inputs on voltmeters or three /5A or /1A current inputs on ammeters.
The dimensions are 96x96mm, with a depth of just 41.5mm.
Standard types can be powered by AC (80...270V~) and DC (80...270V dc) systems.
Both also offer the special 18 ... 36V dc power supply option.

Application

Measurement of basic electrical parameters in switchboards and low- and medium-voltage connections where space constraints require installing an accurate, space-saving panel indicactor.

Creation date: 23/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



DCP-96 VAC

Panel-mounted digital instruments

Code: M22410.

Specifications

AC power supply

Installation category	CAT III 300 V
Consumption	1 ... 4 VA
Frequency	50/60 Hz
Nominal voltage	80 ... 270 Vac

DC power supply

Installation category	CAT III 300 V
Consumption	0.5 ... 0.7 W
Nominal voltage	80...270 Vdc

Mechanical characteristics

Size (mm) width x height x depth	96 x 96 x 41.5 (mm)
Envelope	Polycarbonate + ABS
Weight (kg)	0,3

Environmental characteristics

Protection class	Front: IP54, Rear: IP20
Relative humidity (without condensation)	≤ 95%
Storage temperature	-40... +85 °C
Working temperature	-25 ... +70°C

Voltage measurement circuit

Installation category	CAT III 300 V
Consumption	< 0.2 VA (por fase)
Sampling frequency	45...65 Hz
Input impedance	> 1.7 MΩ
Frequency measuring range	45 ... 65 Hz
Voltage measuring range	45 ... 65 Hz
Nominal voltage	100...277 V~ Ph-N (± 8%)
Maximum permanent measurement voltage	1.2 Un continuous, 2 Un instantaneous (1 min)

Standards

Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300 V
Electrical safety, Contamination level/class	Pollution resistance 2
Standards	IEC 61010-1, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11

Creation date: 23/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



DCP-96 VAC

Panel-mounted digital instruments

Code: M22410.

User interface

Keyboard	3 keys
Display type	LCD

Measurement accuracy

Frequency measurement	± 0.01 Hz
Phase voltage measurement	0.2 % (± 1 digit)

Creation date: 23/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.




DCP-96 VAC

Panel-mounted digital instruments

Code: M22410.

Connections



Creation date: 23/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.