



## DCP-96 VAC

DCP-96 VAC, Three-phase digital voltmeter

Code: M22410. DESCATALOGADO

- > Scale: 3 x 230 / 400V
- > System: AC
- > Paramètre: V, Hz
- > Mounting: Pannel
- > Modules: 96 x 96

### Application

Measurement of basic electrical parameters in switchboards and low- and medium-voltage connections where space constraints require installing an accurate, space-saving panel indicator.



## DCP-96 VAC

Panel-mounted digital instruments

Code: M22410.

### Specifications

#### AC power supply

Installation category	CAT III 300 V
Consumption	1 ... 4 VA
Frequency	50/60 Hz
Nominal voltage	80 ... 270 Vac

#### DC power supply

Installation category	CAT III 300 V
Consumption	0.5 ... 0.7 W
Nominal voltage	80...270 Vdc

#### Mechanical characteristics

Size (mm) width x height x depth	96 x 96 x 41.5 (mm)
Envelope	Polycarbonate + ABS
Weight (kg)	0,3

#### Environmental characteristics

Protection class	Front: IP54, Rear: IP20
Relative humidity (without condensation)	≤ 95%
Storage temperature	-40... +85 °C
Working temperature	-25 ... +70°C

#### Voltage measurement circuit

Installation category	CAT III 300 V
Consumption	< 0.2 VA (por fase)
Sampling frequency	45...65 Hz
Input impedance	> 1.7 MΩ
Frequency measuring range	45 ... 65 Hz
Nominal voltage	100...277 V~ Ph-N (± 8%)
Maximum permanent measurement voltage	1.2 Un continuous, 2 Un instantaneous (1 min)

#### Standards

Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300 V
Electrical safety, Contamination level/class	Pollution resistance 2
Standards	IEC 61010-1, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11

#### User interface



## DCP-96 VAC

Panel-mounted digital instruments

Code: M22410.

Keyboard	3 keys
Display type	LCD

### Measurement accuracy

Frequency measurement	$\pm 0.01$ Hz
Phase voltage measurement	0.2 % ( $\pm 1$ digit)



# DCP-96 VAC

Panel-mounted digital instruments

Code: M22410.

## Connections

