

MK30-DC

MK30-DC, Energy meter

Code: M30300. **DESCATALOGADO**

> Módules: 2
> Tariff: 1
> Measurement Range (V): 0...800
> Measure: 30 Adc
> Paramètre: V, A, kW, kWh
> Display: LED de 7 segmentos y 4 dígitos

Description

Electronic energy meter of direct current for DIN rails.

Other features include:

- Voltage up to 800 Vdc.
- 4-digit display with 7 red segments, highly efficient.
- 2-module size.
- Parameters measured: V, A, kW, kWh
- 1 digital output with opto-coupled transistor.

Application

- Energy metering of direct current that can be used to control the energy consumed and the energy generated in solar power farms.
- Energy control in telecommunications installations for subsequent management.

Creation date: 30/10/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



MK30-DC

Electronic energy meter of direct current for DIN rail mounting

Code: M30300.

Specifications

Mechanical characteristics

Size (mm) width x height x depth	30 x 85 x 63.8 (mm)
Weight (kg)	0,19

Applications for the photovoltaic power ind. (*) for shunt connections

Creation date: 30/10/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.