

### LM4A-210-M

LM4A-2IO-M, Impulse centraliser

#### Code: M31565. DESCATALOGADO

- > Protocol: Modbus/RTU
- > Analogue Inputs: 4 (0...20mA)
- > Módules: 4
- > Communications: RS-485
- > N° relays: 2
- > Digital inputs: 2

### Description

The LM4 is an digital and/or analogue signals centralizer (depending type).

The unit includes an RS- 485 communications bus with a Modbus/ RTU protocol, which allows real time control by communications. The unit is compatible with PowerStudio and PowerStudio SCADA control software.

Other features of LM4A-2IO-M:

- Telemanagement of the 2 digital outputs
- $\circ~$  Supervision of the 2 digital inputs
- Monitoring of the 4 analogue inputs

#### Application

Reading of any pulse-emitting meter (up to 4 devices). These parameters are useful for generating bills or for specifying a price/unit cost

- The outputs available on the device can control contacts (gas, water, steam, etc.), and sound and/or light devices to provide protection or alarms by using an internal relay.
- Detection of logical states for electrical switching or alarms that can control relays through software or modbus communications.

Circutor

Page 1 of 4

Page 2 of 4



LM4A-210-M

Impulse centralizing unit

Code: M31565.

### Specifications

AC power supply	
Consumption	3,5 VA
Frequency	47 63 Hz
Nominal voltage	85265 Vca / 120 374 Vcc
Mechanical characteristics	
Size (mm) width x height x depth	71 x 93 x 58 (mm)
Envelope	Plastic UL 94 - VO self-extinguishing
Fastening	DIN rail
Weight (kg)	0,133
Environmental characteristics	
Protection class	IP 20
Relative humidity (without condensation)	595%
Working temperature	-10 +60 °C
Standards	
Certifications	CE, UL, VDE
Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300V / 520V, IEC 61010
Standards	IEC 60664, VDE 0110, UL 94, EN-61010-1, EN 55011, EN 61000-4-3, EN 61000-4-11, EN 61000-6-4, EN 61000-4-2, EN 61000-6-2, EN 61000-6-1, EN 61000-6-3, EN 61000-4-5
Communication Network	
Technology / Type	Ethernet 10BaseT/100BaseTX auto-detecting
Electrical safety	
Insulation	Double-insulated electric shock protection class II (IEC 61010-1)
Analogue inputs	
Quantity	4
Input impedance	100 Ω
Nominal range	0 20 mA
Measurement type	Current analog
Digital inputs	
Quantity	2
Туре	Free of optoisolated voltage

Circutor



### LM4A-210-M

Impulse centralizing unit

Code: M31565.

Maximum short-circuit current	50 mA
Digital relay outputs	
Quantity	2
Туре	Relay
Maximum open contact voltage	250 V ~
Electrical life	3 x 10 <sup>4</sup> (250 Vca / 5 A)
Mechanical life	2 x 10 <sup>7</sup>
Maximum switching capacity	750 VA

(\*) Digital inputs (logic 0 / 1) or energy impulses

# Circutor



## LM4A-210-M

Impulse centralizing unit

Code: M31565.

## Dimensions

## Connections

×

×

